

Silicon NPN Power Transistors

2SC4235

DESCRIPTION

- With TO-247 package
- Switching power transistor
- High breakdown voltage

PINNING

PIN	DESCRIPTION
1	Base
2	Collector;connected to mounting base
3	Emitter




Fig.1 simplified outline (TO-247) and symbol

Absolute maximum ratings($T_c=25^\circ\text{C}$)

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
V_{CBO}	Collector-base voltage	Open emitter	1200	V
V_{CEO}	Collector-emitter voltage	Open base	800	V
V_{EBO}	Emitter-base voltage	Open collector	7	V
I_C	Collector current (DC)		3	A
I_{CM}	Collector current-Peak		6	A
I_B	Base current		1	A
I_{BM}	Base current-Peak		2	A
P_D	Total power dissipation	$T_c=25^\circ\text{C}$	80	W
T_j	Junction temperature		150	$^\circ\text{C}$
T_{stg}	Storage temperature		-55~150	$^\circ\text{C}$

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
$R_{th\ j-C}$	Thermal resistance junction to case	1.56	$^\circ\text{C}/\text{W}$

Silicon NPN Power Transistors

2SC4235

CHARACTERISTICS

Tj=25°C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
$V_{CEO(SUS)}$	Collector-emitter sustaining voltage	$I_C=0.1A; I_B=0$	800			V
V_{CEsat}	Collector-emitter saturation voltage	$I_C=1.5A; I_B=0.3A$			1.0	V
V_{BEsat}	Base-emitter saturation voltage	$I_C=1.5A; I_B=0.3A$			1.5	V
I_{CBO}	Collector cut-off current	At rated voltage			0.1	mA
I_{CEO}	Collector cut-off current					
I_{EBO}	Emitter cut-off current	At rated voltage			0.1	mA
h_{FE-1}	DC current gain	$I_C=1.5A; V_{CE}=5V$	8			
h_{FE-2}	DC current gain	$I_C=1mA; V_{CE}=5V$	7			
f_T	Transition frequency	$I_C=0.3A; V_{CE}=10V$		8		MHz

Switching times resistive load

t_{on}	Turn-on time	$I_C=1.5A$ $I_{B1}=0.3A; I_{B2}=0.6A$ $V_{BB2}=4V, R_L=170\Omega$			0.5	μs
t_s	Storage time				3.5	μs
t_f	Fall time				0.3	μs

2SC4235