



2SD1554


NPN TRIPLE DIFFUSED
PLANAR SILICON TRANSISTOR

COLOR TV HORIZONTAL OUTPUT
APPLICATIONS(Damper Diode BUILT IN)

- High Collector-Base Voltage($V_{CBO}=1500V$)
- High Speed Switching

ABSOLUTE MAXIMUM RATINGS ($T_A=25^{\circ}C$)

Characteristic	Symbol	Rating	Unit
Collector-Base Voltage	V_{CBO}	1500	V
Collector-Emitter Voltage	V_{CEO}	1500	V
Emitter-Base voltage	V_{EBO}	6	V
Collector Current (DC)	I_C	3.5	A
Collector Dissipation ($T_c=25^{\circ}C$)	P_C	50	W
Junction Temperature	T_j	150	$^{\circ}C$
Storage Temperature	T_{stg}	-50~150	$^{\circ}C$



ELECTRICAL CHARACTERISTICS ($T_A=25^{\circ}C$)

Characterristic	Symbol	Test Condition	Min	Typ	Max	Unit
Collector- Emitter Cutoff Current($V_{BE}=0$)	I_{CES}	$V_{CE}=1400\text{ V}$, $R_{BE}=0$	8		1.0	mA
Collector Cutoff Current	I_{CBO}				10	μA
Emitter Cutoff Current	I_{EBO}	$V_{CB}=800\text{ V}$, $I_E=0$			1.0	mA
DC Current Gain	h_{FE}	$V_{EB}=4\text{ V}$, $I_C=0$				
Collector- Emitter Saturation Voltage	$V_{CE(sat)}$	$V_{CE}=5\text{ V}$, $I_C=1A$ $I_C=3A$, $I_B=0.8A$			8.0	V