

Ordering number: EN 3449A

SANYO	No.3449A	2SK1446
		N-Channel Silicon MOSFET Ultrahigh-Speed Switching Applications

Features

- Low ON-state resistance.
- Ultrahigh-speed switching.
- Micaless package facilitating easy mounting.

Absolute Maximum Ratings at Ta = 25°C

			unit
Drain-to-Source Voltage	V _{DSS}	450	V
Gate-to-Source Voltage	V _{GSS}	±30	V
Drain Current(DC)	I _D	7	A
Drain Current(Pulse)	I _{DP}	28	A
Allowable Power Dissipation	P _D	2.0	W
		35	W
Channel Temperature	T _{ch}	150	°C
Storage Temperature	T _{stg}	-55 to +150	°C


T_c = 25°C

Electrical Characteristics at Ta = 25°C

			min	typ	max	unit
D-S Breakdown Voltage	V _{(BR)DSS}	I _D = 1mA, V _{GS} = 0	450			V
Zero-Gate Voltage Drain Current	I _{DSS}	V _{DS} = 450V, V _{GS} = 0			1.0	mA
Gate-to-Source Leakage Current	I _{GSS}	V _{GS} = ±30V, V _{DS} = 0			±100	nA
Cutoff Voltage	V _{GS(off)}	V _{DS} = 10V, I _D = 1mA	2.0		3.0	V
Forward Transfer Admittance	Y _{fs}	V _{DS} = 10V, I _D = 4A	3.0	6.0		S
Static Drain-to-Source ON-State Resistance	R _{DS(on)}	I _D = 4A, V _{GS} = 10V		0.6	0.8	Ω
Input Capacitance	C _{iss}	V _{DS} = 20V, f = 1MHz		1200		pF
Output Capacitance	C _{oss}	V _{DS} = 20V, f = 1MHz		180		pF
Reverse Transfer Capacitance	C _{rss}	V _{DS} = 20V, f = 1MHz		70		pF
Turn-ON Delay Time	t _{d(on)}	I _D = 4A, V _{GS} = 10V V _{DD} = 200V, R _{GS} = 50Ω		20		ns
Rise Time	t _r		40		ns	
Turn-OFF Delay Time	t _{d(off)}		160		ns	
Fall Time	t _f		60		ns	
Diode Forward Voltage	V _{SD}	I _S = 7A, V _{GS} = 0			1.8	V


(Note) Be careful in handling the 2SK1446 because it has no protection diode between gate and source.

Switching Time Test Circuit



Package Dimensions 2078B

(unit : mm)











- 1: Gate
- 2: Drain
- 3: Source

SANYO : TO-220FI(LS)





SANYO Electric Co., Ltd. Semiconductor Business Headquarters
TOKYO OFFICE Tokyo Bldg., 1-10, 1 Chome, Ueno, Taito-ku, TOKYO, 110 JAPAN

72597TS (KOTO)/7151JN (KOTO) No.3449-1/3

2SK1446



2SK1446



Electrónica S.A. de C.V.

■ No products described or contained herein are intended for use in surgical implants, life-support systems, aerospace equipment, nuclear power control systems, vehicles, disaster/crime-prevention equipment and the like, the failure of which may directly or indirectly cause injury, death or property loss.

■ Anyone purchasing any products described or contained herein for an above-mentioned use shall:

- ① Accept full responsibility and indemnify and defend SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors and all their officers and employees, jointly and severally, against any and all claims and litigation and all damages, cost and expenses associated with such use;
- ② Not impose any responsibility for any fault or negligence which may be cited in any such claim or litigation on SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors or any of their officers and employees jointly or severally.

■ Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.

This catalog provides information as of July, 1997. Specifications and information herein are subject to change without notice.