

International IR Rectifier

70HF(R) SERIES

STANDARD RECOVERY DIODES


Stud Version

Features

- High surge current capability
- Designed for a wide range of applications
- Stud cathode and stud anode version
- Leaded version available
- Types up to 1600V V_{RRM}

Typical Applications

- Battery charges
- Converters
- Power supplies
- Machine tool controls



Major Ratings and Characteristics

Parameters	70HF(R)		Units	
	10 to 120	140 to 160		
$I_{F(AV)}$	70	70	A	
@ T_C	140	110	°C	
$I_{F(RMS)}$	110		A	
I_{FSM}	@ 50Hz	1200	A	
	@ 60Hz	1250	A	
I^2t	@ 50Hz	7100	A ² s	
	@ 60Hz	6540	A ² s	
V_{RRM}	range	100 to 1200	1400 to 1600	V
T_J	range	- 65 to 180	- 65 to 150	°C



70HF(R) Series

Bulletin I20202 rev. A 05/98

International
IR Rectifier**ELECTRICAL SPECIFICATIONS**

Voltage Ratings

Type number	Voltage Code	V _{RRM} [*] maximum repetitive peak reverse voltage V	V _{RSM} [*] maximum non-repetitive peak reverse voltage V	V _{R(BR)} , minimum avalanche voltage V (1)	I _{RRM} max. @ T _J = T _J max. mA
70HF(R)	10	100	200	--	15
	20	200	300	--	
	40	400	500	500	
	60	600	720	725	9
	80	800	960	950	
	100	1000	1200	1150	
	120	1200	1440	1350	
	140	1400	1650	1550	4.5
	160	1600	1900	1750	

(1) Avalanche version only available from V_{RRM} 400V to 1600V.

Forward Conduction

Parameter	70HF(R)		Units	Conditions
	10 to 120	140 to 160		
I _{F(AV)} Max. average forward current @ Case temperature	70	70	A	180° conduction, half sine wave
I _{F(RMS)} Max. RMS forward current	140	110	A	DC @ T _C = 25°C
P _R Maximum non-repetitive peak reverse power	20		K·W	10µs square pulse, T _J = T _J max. see note (2)
I _{FSM} Max. peak, one-cycle forward, non-repetitive surge current	1200		A	t = 10ms No voltage
	1250			t = 8.3ms reapplied
	1000			t = 10ms 100% V _{RRM}
	1050			t = 8.3ms reapplied
I ² t Maximum I ² t for fusing	7100		A ² s	t = 10ms No voltage
	6450			t = 8.3ms reapplied
	5000			t = 10ms 100% V _{RRM}
	4550			t = 8.3ms reapplied
I ² √t Maximum I ² √t for fusing	71000		A ² √s	t = 0.1 to 10ms, no voltage reapplied
V _{F(TO)1} Low level value of threshold voltage	0.79		V	(16.7% × π × I _{F(AV)} < I < π × I _{F(AV)}), T _J = T _J max.
V _{F(TO)2} High level value of threshold voltage	1.00			(I > π × I _{F(AV)}), T _J = T _J max.
r _{f1} Low level value of forward slope resistance	2.33		mΩ	(16.7% × π × I _{F(AV)} < I < π × I _{F(AV)}), T _J = T _J max.
r _{f2} High level value of forward slope resistance	1.53			(I > π × I _{F(AV)}), T _J = T _J max.
V _{FM} Max. forward voltage drop	1.35		V	I _{pk} = 220A, T _J = 25°C, t _p = 10ms sinusoidal wave

(2) Available only for Avalanche version, all other parameters the same as 70HF.

Thermal and Mechanical Specifications

Parameter	70HF(R)		Units	Conditions
	10 to 120	140 to 160		
T _J Max. junction operating temperature range	-65 to 180	-65 to 150	°C	
T _{stg} Max. storage temperature range	-65 to 180	-65 to 150		
R _{thJC} Max. thermal resistance, junction to case	0.45		K/W	DC operation
R _{thCS} Max. thermal resistance, case to heatsink	0.25			Mounting surface, smooth, flat and greased
T Max. allowed mounting torque ±10%	2.3 - 3.4		Nm	Not lubricated threads
	20 - 30		lbf·in	
wt Approximate weight	17 (0.6)		g (oz)	
Case style	DO-203AB (DO5)		See Outline Table	

ΔR_{thJC} Conduction

(The following table shows the increment of thermal resistance R_{thJC} when devices operate at different conduction angles than DC)

Conduction angle	Sinusoidal conduction	Rectangular conduction	Units	Conditions
180°	0.08	0.06	K/W	T _J = T _J max.
120°	0.10	0.11		
90°	0.13	0.14		
60°	0.19	0.20		
30°	0.30	0.30		

Ordering Information Table


Device Code											
	<table border="1" style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 5px;">70</td> <td style="padding: 5px;">HF</td> <td style="padding: 5px;">R</td> <td style="padding: 5px;">160</td> <td style="padding: 5px;">M</td> </tr> <tr> <td style="text-align: center;">1</td> <td style="text-align: center;">2</td> <td style="text-align: center;">3</td> <td style="text-align: center;">4</td> <td style="text-align: center;">5</td> </tr> </table>	70	HF	R	160	M	1	2	3	4	5
70	HF	R	160	M							
1	2	3	4	5							
1	- 70 = Standard device - 71 = Not isolated lead - 72 = Isolated lead with silicone sleeve (Red = Reverse polarity) (Blue = Normal polarity)										
2	- HF = Standard diode - HA = Avalanche diode										
3	- None = Stud Normal Polarity (Cathode to Stud) - R = Stud Reverse Polarity (Anode to Stud)										
4	- Voltage code: Code x 10 = V _{RRM} (See Voltage Ratings table)										
5	- None = Stud base DO-203AB (DO-5) 1/4" 28UNF-2A - M = Stud base DO-203AB (DO-5) M6 X 1 - (Not available for Avalanche diodes)										

70HF(R) Series

Bulletin I20202 rev. A 05/98

International
IRF Rectifier

Outlines Table






Fig. 1 - Current Ratings Characteristics




Fig. 2 - Current Ratings Characteristics




Fig. 3 - Current Ratings Characteristics




Fig. 4 - Current Ratings Characteristics




Fig. 5 - Forward Power Loss Characteristics

70HF(R) Series

Bulletin I20202 rev. A 05/98

International
IR Rectifier




Fig. 6 - Forward Power Loss Characteristics




Fig. 7 - Forward Power Loss Characteristics




Fig. 8 - Forward Power Loss Characteristics




Fig. 9 - Maximum Non-Repetitive Surge Current




Fig. 10 - Maximum Non-Repetitive Surge Current




Fig. 11 - Forward Voltage Drop Characteristics




Fig. 12 - Thermal Impedance Z_{thJC} Characteristics

Electrónica S.A. de C.V.