

Product Overview

AR0132AT: CMOS Image Sensor, 1.2 MP, 1/3"

For complete documentation, see the [data sheet](#).

ON Semiconductor's AR0132AT 1/3-inch CMOS digital image sensor with an active-pixel array of 1280H x 960V. It captures images in either linear or high dynamic range modes, with a rolling-shutter readout. It includes sophisticated camera functions such as auto exposure control, windowing, and both video and single frame modes. It is designed for both low light and high dynamic range scene performance. It is programmable through a simple two-wire serial interface. The AR0132AT produces extraordinarily clear, sharp digital pictures, and its ability to capture both continuous video and single frames makes it the perfect choice for a wide range of applications, including surveillance and HD video. This sensor is compatible with ON Semiconductor's automotive image co-processors which provides megapixel HDR image processing.

Features

- High Dynamic Range

Applications

- Automotive

Part Electrical Specifications

Product	Pricing (\$/Unit)	Compliance	Status	Type	Megapix els	Frame Rate (fps)	Optical Format	Shutter Type	Pixel Size (µm)	Output Interface	Color	Package Type
AR0132AT6B00XPD20		AEC Qualified PPAP Capable Pb-free Halide free	Active	CMOS	1.2	60	1/3 inch	Electroni c Rolling	3.75 x 3.75	-	Mono RGB	
AR0132AT6C00XPD20		AEC Qualified PPAP Capable Pb-free Halide free	Active	CMOS	1.2	60	1/3 inch	Electroni c Rolling	3.75 x 3.75	-	Mono RGB	
AR0132AT6C00XPEA0- DPBR		AEC Qualified PPAP Capable Pb-free Halide free	Active	CMOS	1.2	60	1/3 inch	Electroni c Rolling	3.75 x 3.75	-	RGB	IBGA-63
AR0132AT6C00XPEA0- DRBR		AEC Qualified PPAP Capable Pb-free Halide free	Active	CMOS	1.2	60	1/3 inch	Electroni c Rolling	3.75 x 3.75	-	RGB	IBGA-63
AR0132AT6C00XPEA0- DRBR1		AEC Qualified PPAP Capable Pb-free Halide free	Active	CMOS	1.2	60	1/3 inch	Electroni c Rolling	3.75 x 3.75	-	RGB	IBGA-63
AR0132AT6C00XPEA0- TPBR		AEC Qualified PPAP Capable Pb-free Halide free	Active	CMOS	1.2	60	1/3 inch	Electroni c Rolling	3.75 x 3.75	-	RGB	IBGA-63
AR0132AT6C00XPEA0- TRBR		AEC Qualified PPAP Capable Pb-free Halide free	Active	CMOS	1.2	60	1/3 inch	Electroni c Rolling	3.75 x 3.75	-	RGB	IBGA-63
AR0132AT6G00XPEA0- AA-DRBR		AEC Qualified PPAP Capable Pb-free Halide free	Active	CMOS	1.2	60	1/3 inch	Electroni c Rolling	3.75 x 3.75	-	Mono RGB	IBGA-63
AR0132AT6M00XPEA0- DPBR		AEC Qualified PPAP Capable Pb-free Halide free	Active	CMOS	1.2	60	1/3 inch	Electroni c Rolling	3.75 x 3.75	-	Mono	IBGA-63
AR0132AT6M00XPEA0- DRBR		AEC Qualified PPAP Capable Pb-free Halide free	Active	CMOS	1.2	60	1/3 inch	Electroni c Rolling	3.75 x 3.75	-	Mono	IBGA-63
AR0132AT6M00XPEA0- DRBR1		AEC Qualified PPAP Capable Pb-free Halide free	Active	CMOS	1.2	60	1/3 inch	Electroni c Rolling	3.75 x 3.75	-	Mono	IBGA-63

AR0132AT6M00XPEA0-TPBR		AEC Qualified PPAP Capable Pb-free Halide free	Active	CMOS	1.2	60	1/3 inch	Electronic Rolling	3.75 x 3.75	-	Mono	IBGA-63
AR0132AT6R00XPEA0-DPBR		AEC Qualified PPAP Capable Pb-free Halide free	Active	CMOS	1.2	60	1/3 inch	Electronic Rolling	3.75 x 3.75	-	Other	IBGA-63
AR0132AT6R00XPEA0-DPBR1		AEC Qualified PPAP Capable Pb-free Halide free	Active	CMOS	1.2	60	1/3 inch	Electronic Rolling	3.75 x 3.75	-	Other	IBGA-63
AR0132AT6R00XPEA0-DRBR		AEC Qualified PPAP Capable Pb-free Halide free	Active	CMOS	1.2	60	1/3 inch	Electronic Rolling	3.75 x 3.75	-	Other	IBGA-63
AR0132AT6R00XPEA0-DRBR1		AEC Qualified PPAP Capable Pb-free Halide free	Active	CMOS	1.2	60	1/3 inch	Electronic Rolling	3.75 x 3.75	-	Other	IBGA-63
AR0132AT6R00XPEA0-TB-DPBR		AEC Qualified PPAP Capable Pb-free Halide free	Active									IBGA-63
AR0132AT6R00XPEA0-TPBR		AEC Qualified PPAP Capable Pb-free Halide free	Active	CMOS	1.2	60	1/3 inch	Electronic Rolling	3.75 x 3.75	-	Other	IBGA-63
AR0132AT6R00XPEA0-TRBR		AEC Qualified PPAP Capable Pb-free Halide free	Active	CMOS	1.2	60	1/3 inch	Electronic Rolling	3.75 x 3.75	-	Other	IBGA-63
AR0132AT6R00XPEA0-TRBR-E		Pb-free Halide free	Active	CMOS	1.2	60	1/3 inch	Electronic Rolling	3.75 x 3.75	-	RGB and Mono	IBGA-63

For more information please contact your local sales support at www.onsemi.com.

Created on: 1/12/2020