



Certificate Number: Q10561



Certificate Number: E17276

AR3500L - AR3510L

PRV : 50 - 1000 Volts

Io : 35 Amperes

FEATURES :

- * High current capability
- * High surge current capability
- * High reliability
- * Low reverse current
- * Low forward voltage drop

MECHANICAL DATA :

- * Case : Molded plastic
- * Epoxy : UL94V-O rate flame retardant
- * Lead : Axial lead solderable per MIL-STD-202,
Method 208 guaranteed
- * Polarity : Cathode polarity band
- * Mounting position : Any
- * Weight : 2.73 grams


MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25 °C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load.

For capacitive load, derate current by 20%.

AUTOMOTIVE RECTIFIER DIODES



RATING	SYMBOL	AR 3500L	AR 3501L	AR 3502L	AR 3504L	AR 3506L	AR 3508L	AR 3510L	UNIT
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	50	100	200	400	600	800	1000	Volts
Maximum RMS Voltage	V_{RMS}	35	70	140	280	420	560	700	Volts
Maximum DC Blocking Voltage	V_{DC}	50	100	200	400	600	800	1000	Volts
Average Rectified Forward Current $T_c = 150^{\circ}\text{C}$	$I_{F(AV)}$	35							Amps.
Peak Forward Surge Current Single half sine wave superimposed on rated load (JEDEC Method)	I_{FSM}	400							Amps.
Maximum Forward Voltage at $I_F = 35$ Amps.	V_F	1.1							Volts
Maximum DC Reverse Current $T_a = 25^{\circ}\text{C}$ at rated DC Blocking Voltage $T_a = 100^{\circ}\text{C}$	I_R	5.0							μA
	$I_{R(H)}$	1.0							mA
Thermal Resistance (Note 1)	$R_{\theta JC}$	1.0							$^{\circ}\text{C/W}$
Junction Temperature Range	T_J	- 65 to + 175							$^{\circ}\text{C}$
Storage Temperature Range	T_{STG}	- 65 to + 175							$^{\circ}\text{C}$

Note : (1) Thermal resistance from junction to case. Single side cooled.

UPDATE : APRIL 23, 1998

RATING AND CHARACTERISTIC CURVES (AR3500L - AR3510L)

FIG.1 - DERATING CURVE FOR OUTPUT RECTIFIED CURRENT




FIG.2 - MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3 - TYPICAL FORWARD CHARACTERISTICS




FIG.4 - TYPICAL REVERSE CHARACTERISTICS

