


**BYV26DGP & BYV26EGP**

Vishay General Semiconductor

**Glass Passivated Ultrafast Rectifier**

\* Glass Encapsulation technique is covered by Patent No. 3,996,602, brazed-lead assembly to Patent No. 3,930,306

**DO-204AC (DO-15)****FEATURES**

- Cavity-free glass-passivated junction
- Ultrafast reverse recovery time
- Low forward voltage drop
- Low switching losses, high efficiency
- High forward surge capability
- Meets environmental standard MIL-S-19500
- Solder dip 260 °C, 40 s
- Component in accordance to RoHS 2002/95/EC and WEEE 2002/96/EC



**RoHS**  
COMPLIANT

**TYPICAL APPLICATIONS**

For use in high frequency rectification and freewheeling application in switching mode converters and inverters for consumer, computer and telecommunication.

**MECHANICAL DATA**

**Case:** DO-204AC, molded epoxy over glass body

Epoxy meets UL 94V-0 flammability rating

**Terminals:** Matte tin plated leads, solderable per J-STD-002 and JESD22-B102

E3 suffix for consumer grade, meets JESD 201 class 1A whisker test, HE3 suffix for high reliability grade (AEC Q101 qualified), meets JESD 201 class 2 whisker test

**Polarity:** Color band denotes cathode end

<b>PRIMARY CHARACTERISTICS</b>	
$I_{F(AV)}$	1.0 A
$V_{RRM}$	800 V, 1000 V
$I_{FSM}$	30 A
$t_{rr}$	75 ns
$V_F$	1.3 V
$T_J \text{ max.}$	175 °C

<b>MAXIMUM RATINGS</b> ( $T_A = 25\text{ °C}$ unless otherwise noted)				
PARAMETER	SYMBOL	BYV26DGP	BYV26EGP	UNIT
Maximum repetitive peak reverse voltage	$V_{RRM}$	800	1000	V
Maximum RMS voltage	$V_{RMS}$	560	700	V
Maximum DC blocking voltage	$V_{DC}$	800	1000	V
Maximum average forward rectified current 0.375" (9.5 mm) lead length (Fig. 1)	$I_{F(AV)}$	1.0		A
Peak forward surge current 10 ms single half sine-wave superimposed on rated load	$I_{FSM}$	30		A
Non repetitive peak reverse energy <sup>(1)</sup>	$E_{RSM}$	10		mJ
Operating junction and storage temperature range	$T_J, T_{STG}$	- 65 to + 175		°C

**Note:**

(1) Peak reverse energy measured at  $I_R = 400\text{ mA}$ ,  $T_J = T_J \text{ max.}$  on inductive load,  $t = 20\text{ }\mu\text{s}$

# BYV26DGP & BYV26EGP

Vishay General Semiconductor

<b>ELECTRICAL CHARACTERISTICS</b> ( $T_A = 25\text{ }^{\circ}\text{C}$ unless otherwise noted)					
PARAMETER	TEST CONDITIONS		SYMBOL	BYV26DGP	BYV26EGP
Minimum avalanche breakdown voltage	100 $\mu\text{A}$		$V_{BR}$	900	1100
Maximum instantaneous forward voltage	1.0 A	$T_J = 25\text{ }^{\circ}\text{C}$ $T_J = 175\text{ }^{\circ}\text{C}$	$V_F$	2.5 1.3	
Maximum DC reverse current at rated DC blocking voltage		$T_A = 25\text{ }^{\circ}\text{C}$ $T_A = 165\text{ }^{\circ}\text{C}$	$I_R$	5.0 150	
Max. reverse recovery time	$I_F = 0.5\text{ A}$ , $I_R = 1.0\text{ A}$ , $t_{rr} = 0.25\text{ A}$		$t_{rr}$	75	
Typical junction capacitance	4.0 V, 1 MHz		$C_J$	15	

<b>THERMAL CHARACTERISTICS</b> ( $T_A = 25\text{ }^{\circ}\text{C}$ unless otherwise noted)				
PARAMETER	SYMBOL	BYV26DGP	BYV26EGP	UNIT
Typical thermal resistance <sup>(1)(2)</sup>	$R_{\theta JA}$ $R_{\theta JL}$	70 16		$^{\circ}\text{C/W}$

## Notes:

- (1) Thermal resistance from junction to ambient at 0.375" (9.5 mm) lead length, mounted on P.C.B. with 0.5 x 0.5" (12 x 12 mm) copper pads  
 (2) Thermal resistance from junction to lead at 0.375" (9.5 mm) lead length with both leads attached to heatsink

<b>ORDERING INFORMATION</b> (Example)				
PREFERRED P/N	UNIT WEIGHT (g)	PREFERRED PACKAGE CODE	BASE QUANTITY	DELIVERY MODE
BYV26EGP-E3/54	0.428	54	4000	13" diameter paper tape and reel
BYV26EGP-E3/73	0.428	73	2000	Ammo pack packaging
BYV26EGPHE3/54 <sup>(1)</sup>	0.428	54	4000	13" diameter paper tape and reel
BYV26EGPHE3/73 <sup>(1)</sup>	0.428	73	2000	Ammo pack packaging

## Note:

- (1) Automotive grade AEC Q101 qualified

## RATINGS AND CHARACTERISTICS CURVES

( $T_A = 25\text{ }^{\circ}\text{C}$  unless otherwise noted)




Figure 1. Maximum Forward Current Derating Curve




Figure 2. Forward Power Loss Characteristics

**BYV26DGP & BYV26EGP**

Vishay General Semiconductor




Figure 3. Maximum Non-Repetitive Peak Forward Surge Current




Figure 6. Typical Junction Capacitance




Figure 4. Typical Instantaneous Forward Voltage Characteristics




Figure 7. Typical Transient Thermal Impedance





Figure 5. Typical Reverse Leakage Characteristics

**BYV26DGP & BYV26EGP**

Vishay General Semiconductor

**PACKAGE OUTLINE DIMENSIONS** in inches (millimeters)**DO-204AC (DO-15)***Electrónica S.A. de C.V.*

## Legal Disclaimer Notice

---

Vishay

### Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

*Electrónica S.A. de C.V.*