

Features

- RoHS compliant*
- Low capacitance - 0.55 pF
- ESD protection >15 kV
- Protects 4 I/O and 1 V_{DD} line

Applications


- HDMI 1.4
- Digital Visual Interface (DVI)
- USB 3.0 / USB OTG
- Memory protection
- SIM card ports

CDSOT236-0504LC - TVS/Steering Diode Array

General Information

The CDSOT236-0504LC device provides ESD, EFT and Surge protection for high speed data ports meeting IEC 61000-4-2 (ESD), IEC 61000-4-4 (EFT) and IEC 61000-4-5 (Surge) requirements. The Transient Voltage Suppressor array offers a Working Peak Reverse Voltage of 5 V and Minimum Breakdown Voltage of 6 V.

The SOT23-6L packaged device will mount directly onto the industry standard SOT23-6L footprint. Bourns® Chip Diodes are easy to handle with standard pick and place equipment and their flat configuration minimizes roll away.



Thermal Characteristics (@ T_A = 25 °C Unless Otherwise Noted)

| Parameter | Symbol | CDSOT236-0504LC | Unit |
|--|----------------------|-------------------------------------|------|
| Peak Pulse Current (t _p = 8/20 μs) | I _{PP} | 4.7 | A |
| Storage Temperature | T _{STG} | -55 to +150 | °C |
| Operating Temperature | T _{OPR} | -55 to +85 | °C |
| Operating Supply Voltage | V _{DC} | 6 | V |
| ESD per IEC 61000-4-2 (Air) (I/O Pins) | V _{ESD_IO} | 19 | kV |
| ESD per IEC 61000-4-2 (Contact) (I/O Pins) | | 12 | |
| ESD per IEC 61000-4-2 (Air) (V _{CC} to GND) | V _{ESD_VCC} | 30 | kV |
| ESD per IEC 61000-4-2 (Contact) (V _{CC} to GND) | | 30 | |
| DC Voltage at any I/O Pin | V _{IO} | (GND-0.5) to (V _{CC} +0.5) | V |

Electrical Characteristics (@ T_A = 25 °C Unless Otherwise Noted)

| Parameter | Symbol | CDSOT236-0504LC | Unit |
|--|------------------------|-----------------|------|
| Maximum Reverse Standoff Voltage ¹ | V _{RWM} | 5.0 | V |
| Maximum Leakage Current ¹ @ V _{RWM} | I _L | 5.0 | μA |
| Maximum Channel Leakage Current @ V _{RWM} | I _{CD} | 1.0 | μA |
| Minimum Reverse Breakdown Voltage ¹ @ I _{BV} = 1 mA | V _{BR} | 6.0 | V |
| Maximum Forward Voltage ⁴ @ I _F = 15 mA | V _F | 1.0 | V |
| Typical Clamping Voltage ² | V _C | 8.1 | V |
| Typical ESD Clamping Voltage - I/O ² | V _{clamp_io} | 12 | V |
| Typical ESD Clamping Voltage - V _{CC} ¹ | V _{clamp_VCC} | 9.0 | V |
| Maximum Channel Input Capacitance ² @ V _{PIN5} = 5 V, V _{PIN2} = 0 V, V _{IN} = 2.5 V, f = 1 MHz | C _{IN} | 0.65 | pF |
| Maximum Channel to Channel Input Capacitance ³ @ V _{PIN5} = 5 V, V _{PIN2} = 0 V, V _{IN} = 2.5 V, f = 1 MHz | C _{CROSS} | 0.06 | pF |
| Maximum Variation of Channel Input Capacitance @ V _{PIN5} = 5 V, V _{PIN2} = 0 V, V _{IN} = 2.5 V, f = 1 MHz (I/O Pin to GND) | ΔC _{IN} | 0.06 | pF |

NOTES:

1. Pin 5 to Pin 2 (GND)
2. Pin 1,3,4 or 6 to Pin 2 (GND)
3. Between any two of Pins 1,3,4,6
4. Pin 2 (GND) to Pin 5


*RoHS Directive 2002/95/EC Jan. 27, 2003 including annex and RoHS Recast 2011/65/EU June 8, 2011. Specifications are subject to change without notice. Customers should verify actual device performance in their specific applications.

CDSOT236-0504LC - TVS/Steering Diode Array


BOURNS®

Product Dimensions


This is a molded SOT23-6L package with lead free 100 % Matte Sn on the lead frame. It weighs approximately 3 mg and has a flammability rating of UL 94V-0.



Circuit Diagram



Recommended Footprint



Typical Part Marking

CDSOT236-0504LC54L

How to Order


CD SOT236 - 05 04 LC

Common Code _____
 Chip Diode _____
 Package _____
 SOT236 = SOT23-6L Package _____
 Working Peak Reverse Voltage _____
 05 = 5 V_{RWM} (Volts) _____
 Number of Lines _____
 04 = 4 Data Lines _____
 Suffix _____
 LC = Low Capacitance _____


Specifications are subject to change without notice. Customers should verify actual device performance in their specific applications.

Typical Characteristics


Typical Variation of C_{IN} vs. V_{IN}




Typical Variation of C_{IN} vs. V_{IN}




Typical Variation of C_{IO} to IO vs. V_{IN}




Typical Variation of C_{IO} to IO vs. V_{IN}



Insertion Loss S21 (I/O to GND)



Insertion Loss S21 (I/O to GND)





Specifications are subject to change without notice.
Customers should verify actual device performance in their specific applications.

CDSOT236-0504LC - TVS/Steering Diode Array

BOURNS®

Packaging Information

The product is packaged in tape and reel format per EIA-481 standard.



| Item | Symbol | SOT23-6 |
|------------------------|----------------|---|
| Carrier Width | A | $\frac{3.90 \pm 0.10}{(0.154 \pm 0.004)}$ |
| Carrier Length | B | $\frac{3.90 \pm 0.10}{(0.154 \pm 0.004)}$ |
| Carrier Depth | C | $\frac{0.90 \pm 0.10}{(0.035 \pm 0.004)}$ |
| Sprocket Hole | d | $\frac{1.55 \pm 0.05}{(0.061 \pm 0.002)}$ |
| Reel Outside Diameter | D | $\frac{178}{(7.008)}$ |
| Reel Inner Diameter | D ₁ | $\frac{50.0}{(1.969)}$ MIN. |
| Feed Hole Diameter | D ₂ | $\frac{13.0 \pm 0.20}{(0.512 \pm 0.008)}$ |
| Sprocket Hole Position | E | $\frac{1.75 \pm 0.10}{(0.069 \pm 0.004)}$ |
| Punch Hole Position | F | $\frac{3.50 \pm 0.05}{(0.138 \pm 0.002)}$ |
| Punch Hole Pitch | P | $\frac{4.00 \pm 0.10}{(0.157 \pm 0.004)}$ |
| Sprocket Hole Pitch | P ₀ | $\frac{4.00 \pm 0.10}{(0.157 \pm 0.004)}$ |
| Embossment Center | P ₁ | $\frac{2.00 \pm 0.05}{(0.079 \pm 0.002)}$ |
| Overall Tape Thickness | T | $\frac{0.20 \pm 0.10}{(0.008 \pm 0.004)}$ |
| Tape Width | W | $\frac{8.00 \pm 0.20}{(0.315 \pm 0.008)}$ |
| Reel Width | W ₁ | $\frac{14.4}{(0.567)}$ MAX. |
| Quantity per Reel | -- | 3000 |

BOURNS®

Asia-Pacific:

Tel: +886-2 2562-4117

Fax: +886-2 2562-4116

Europe:

Tel: +41-41 768 5555

Fax: +41-41 768 5510

The Americas:

Tel: +1-951 781-5500

Fax: +1-951 781-5700

www.bourns.com

REV. 12/12

Specifications are subject to change without notice.
Customers should verify actual device performance in their specific applications.