

SPECIFICATION



ER26500H 3.6V



Electrical characteristics

(Typical values relative to cells stored for one year at +30 °C max)

◉ Nominal capacity	9000mAh
Discharged capacity at 2mA, +25 °C, 2.0V cut off	
◉ Open circuit voltage	3.66V
◉ Max. recommended continuous current	100mA
Discharged to 2.0V at +25 °C permitting 50% of the nominal capacity to be achieved	
◉ Max. Pulse capability	200mA
200mA, 0.1 second pulses every 2 minutes, drained with 50% 2mA at 25 °C from undischarged cells with 20μA base current, yield voltage readings above 2.7V, the value may vary according to the pulse characteristics, the temperature and the cell's previous history	
◉ Operating temperature rang	-55 °C ~ +85 °C

STORAGE:

Stored in clean, dry and cool circumstances (the temperature should be 20 degrees or lower, less than 30 degrees)

WARNING:

Don't charge, crush, disassemble, expose contents to water, heat above 100°C or may lead to explosion, burn or poison goods leakage. Discarded battery should be buried deeply to the ground.

Key features

- High and stable operating voltage
- Long shelf life
- Annual self-discharge rate lower than 1% at +25 °C
- Long operating life
- High energy density (700wh/kg)
- Wide operating temperature rang
- Stainless steel can and cover
- Hermetic glass-to-metal sealing
- Non-flammable electrolyte
- Compliant with IEC 86-4 safety standard



UL Component Recognition
File Number MH46165


Main applications

- Public instrument
- Alarms or security equipment
- Memory backup
- GPS tracking
- Car electronics
- Professional electronic equipment
- Real time clock



Information in the document is just for reference, not for guarantee of battery performance, the quality of battery is subject to the buyer and seller's final confirmation in the contract.

ER26500H 9000mAh

Discharge characteristics at 25°C



Voltage vs Temperature curve




Dimensions in mm
Weight: 53g

Available Terminations

- | | |
|--------------|---------------|
| - / P* | Axial pin |
| - / T / PT2* | Radial Pin |
| - / PT / TP* | Polarized Tab |
- (*) : Reference to Standard
Terminals for Single Cells

Capacity vs Current curve (cut off with 2.0V)



Discharge characteristics after storage

