

P/N: 72203-0411

Copyright

© 2022, FLIR Systems, Inc.

All rights reserved worldwide. Names and marks appearing herein are either registered trademarks or trademarks of FLIR Systems and/or its subsidiaries. All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

Document identity

Publ. No.: 72203-0411

Commit: 87197

Language:

Modified: 2022-09-21

Formatted: 2022-10-11

Website

<http://www.flir.com>

Customer support

<http://support.flir.com>

Disclaimer

Specifications subject to change without further notice. Camera models and accessories subject to regional market considerations. License procedures may apply. Products described herein may be subject to US Export Regulations. Please refer to exportquestions@flir.com with any questions.



General description	
The FLIR K33 is a robust and reliable infrared camera designed to perform under extremely severe conditions. The FLIR K33 has an intuitive interface with a design that makes it easy to control even with a gloved hand. The crisp and clear image helps you to navigate through smoke and to make quick and accurate decisions.	
Benefits:	
- Robust and reliable: The FLIR K33 is designed to meet tough operating conditions. It can withstand a drop from 2 m (6.5 ft.) onto a concrete floor, is water resistant to IP67, and is fully operational up to +85°C (+185°F), or +260°C (+500°F) for 5 min. - Clear and crisp thermal images: The maintenance-free uncooled microbolometer sensor produces clear and detail-rich images of 240 × 180 pixels which have been further improved with FSX, a digital image processing enhancement technique. Thermal images are presented on a large, bright 4" display, helping you to navigate and to make quick and accurate decisions. - Easy-to-use—also in a gloved firefighter's hand: An intuitive and simple user interface allows you to focus on the job. The FLIR K33 can be controlled by just one large button on top of the unit. Ideal for a gloved firefighter's hand.	

Imaging and optical data	
IR resolution	240 × 180 pixels
Thermal sensitivity/NETD	< 40 mK @ +30°C (+86°F)
Field of view (FOV)	51° × 38°
Depth of field	0.84 m to infinity (33 in. to infinity)
Focal length	9 mm (0.35 in.)
Spatial resolution (IFOV)	3.6 mrad
F-number	1.25
Image frequency	60 Hz
Focus	Fixed

P/N: 72203-0411

© 2022, FLIR Systems, Inc.

#72203-0411; r. 87197;

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–13 μm
Pitch	25 μm
Image presentation	
Display	4 in. LCD, 320 × 240 pixels, backlit
Auto range	Yes, selectable on/off using FLIR K-series camera configurator
Contrast optimization	Digital image enhancement using FSX
Image presentation modes	
Image modes	Basic mode
Measurement	
Object temperature range	–20°C to +150°C (–4°F to +302°F) 0°C to +650°C (+32°F to +1202°F)
Accuracy	±4°C (±7.2°F) or ±4% of reading, for ambient temperature 10°C to 35°C (+50°F to 95°F)
Measurement analysis	
Spotmeter	1
Isotherm	Yes
Set-up	
Set-up commands	Local adaptation of units, date and time formats
Languages	English
Video streaming	
Non-radiometric IR video streaming	Uncompressed colorized video using USB
USB	
USB	USB Mini-B
Data communication interfaces	
Interfaces	- Update from PC devices - Data transfer to and from PC
Power system	
Battery type	Li Ion
Battery voltage	3.6 V
Battery capacity	4.4 Ah, at +20°C to +25°C (+68°F to +77°F)
Battery operating time	Approx. 4 hours at +25°C (+77°F) ambient temperature and typical use
Charging system	- Battery is charged inside the camera 2-bay charger - Optional In-truck charger
Charging time	2 h to 85% capacity, charging status indicated by LEDs

P/N: 72203-0411

© 2022, FLIR Systems, Inc.

#72203-0411; r. 87197;

Power system	
Charging temperature	0°C to +45°C (+32°F to +113°F)
Power management	Automatic shutdown and sleep mode
Start-up time from sleep mode	< 4 s.
Start-up time	< 17 s. (IR image, no GUI)
Battery documents	For documents like MSDS and UN38.3 test reports/summaries, see: https://support.flir.com/resources/msds
Environmental data	
Operating temperature range	–20°C to +85°C (–4°F to +185°F) +150°C (+302°F): 15 min. +260°C (+500°F): 5 min.
Storage temperature range	–40°C to +85°C (–40°F to +185°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
Relative humidity	95% relative humidity +25°C to +40°C (+77°F to +104°F) non-condensing
EMC	- EN 61000-6-2:2005 (Immunity) - EN 61000-6-3: 2011 (Emission) - FCC 47 CFR Part 15 B (Emission)
Magnetic fields	EN 61 000-4-8, Test level 5 for continuous field (severe industrial environment)
Encapsulation	IP 67 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Drop	2 m (6.6 ft.) on concrete floor (IEC 60068-2-31)
Safety (power supply)	CE/EN/UL/CSA/PSE 60950-1
Declaration of conformity	See: https://support.flir.com/resources/DoC
Physical data	
Camera weight, incl. battery	1.1 ±0.05 kg (2.4 ±0.1 lb.)
Battery weight	0.152 kg (0.3 lb.)
Camera size (L × W × H)	120 × 125 × 280 mm (4.7 × 4.9 × 11 in.)
Tripod mounting	UNC ¼"-20 (adapter needed)
Material	- PPSU - Silicon rubber - Aluminium, cast - Flame-resistant magnesium alloy

P/N: 72203-0411


© 2022, FLIR Systems, Inc.

#72203-0411; r. 87197;

Shipping information	
List of contents	• Infrared camera • Battery (2 ea.) • Battery charger • Carabiner strap • Hard transport case • Power supply • Printed documentation • Retractable lanyard, 16 N (58 oz) • USB cable
Packaging, weight	5.7 kg (12.6 lb.)
Packaging, size	500 × 190 × 370 mm (19.7 × 7.5 × 14.6 in.)
EAN-13	7332558011515
UPC-12	845188012465
Country of origin	Estonia

Supplies & accessories:

- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T198125; Battery charger, incl. power supply with multi plugs (Exx, Kxx)
- T127724ACC; Neck strap
- T198416ACC; Lanyard strap
- T198457ACC; Tripod Adapter, Kxx
- T198441ACC; Transport case Kxx
- T198322ACC; In-truck charger
- T199368ACC; Battery Li-ion 3.6 V, 4.4 Ah, 16 Wh
- T129915ACC; Carabiner strap
- T130980ACC; Retractable lanyard, 16 N (58 oz)
- T300466ACC; Battery locking mechanism replacement kit




FLIR SYSTEMS AB
This document must not be communicated or
copied completely or in part, without our permission.
Any infringement will lead to legal proceedings.

Denna handling är ej delades annan, kopieras i
sin helhet eller delar utan vårt medgivande.
Översatta eller återtryckas med stöd av gällande lag.

Konstruktör A. LUND		Datum/Date 2016-03-23	Kontroll/Check	Material	
Ändrad av/Modified by A. LUND		Ändrad/Modified 2016-03-29	Ytfinish/Roughness Ra	Ytbehandling/Surface treatment	
Där ej annat anges/Unless otherwise stated Genom ISO 2768-mK Utmått ut/Excerpt from ISO 2768-m		Benämning/Denomination		Sheet/Sheet Size A3	
0.5-6 80-120 30-120 120-400 400-1000		Hållisradier ±0.1 ±0.2 ±0.3 ±0.5 ±0.8		Scale 1:2	
				ArtNo.	
				Ritning/Drawing No Kx3	
				Rev	



Basic dimension drawing





FLIR SYSTEMS AB
Denna handling får ej delges annan, kopieras
sin helhet eller delar utan vårt medgivande.
Överförelse eller delgivning utan vårt medgivande
kopierad helt eller delvis utan vårt tillstånd.
FLIR SYSTEMS AB
Any infringement will lead to legal proceedings.
This document must not be communicated or

Konstruktör A. LUND	Datum/Date 2016-03-23	Kontroll/Check -	Material -
Ändrad av/Modified by A. LUND	Ändrad/Modified 2016-03-29	Ytjämnhet/Roughness Ra	Ytbehandling/Surface treatment
Benämning/Denomination Basic dimension drawing			
Skala/Scale 1:2	Blad/Sheet 2(2)	ArkNo.	Rev
Rita ritning No Kx3			



Konstr/Drawn P. MARCUS	Datum/Date 2013-04-08	Kontr/Check MABR	Material	
Ändrad av/Modified by P. MARCUS	Ändrad/Modified 2013-04-08	Ytjämnhet/Roughness Ra μm	Ytbehandling/Surface treatment	
Där ej annat anges/Unless otherwise stated Gen tol ISO 2768-mK Utdrag ur/Excerpt from ISO 2768-m	Benämning/Denomination Basic dimensions In-truck charger			Skala/Scale 1:5
0-5-6 $\pm 0,1$ Hålkälsradier (6)-30 $\pm 0,2$ Fillet radii (30)-120 $\pm 0,3$ (120)-400 $\pm 0,5$ Kanter brutna (400)-1000 $\pm 0,8$ Edges broken				Blad/Sheet 1(1)
			Ritn nr/Drawing No T127865	Size A4
				Rev A