

37211250431 - 372 Series



Series: 372 Questions? [Contact Littelfuse Support](#)

[Fuse 372 Datasheet](#)

- Features:
- Lead Free
 - Reduced PCB space requirements
 - Direct solderable or plug-in versions
 - Internationally approved
 - Low internal resistance
 - Shocksafe casing
 - Halogen free

Click on part number below for individual TC curve files.

Check Stock

Order Samples

NEW!
Product Selection Guide eCatalog
[Read Now](#)

Electronics News and Information

SIGN UP NOW

Feedback

| Electrical Characteristics | Technical Resources | Environmental Info |
|---|---------------------------------|--------------------|
| Property (Mouseover for details) | | |
| Value | | |
| Ampere Rating (A) | 1.25 | |
| Nominal Melting I ² T (A ² sec) | 13.8 | |
| Interrupting Rating | 35A@250VAC | |
| Min Operating Temp °C | -40 | |
| Max Operating Temp (°C) | 85 | |
| Moisture Sensitivity Level | MIL-STD-202 Method 106 | |
| Nominal Power Dissipation (W) | 450 | |
| Nominal Voltage Drop (mV) | 95 | |
| Nominal Cold Resistance (Ohms) | 0.055 | |
| Opening | Slo-Blo/Time Lag (T)/Time Delay | |
| Package Size | TR5 (8.5x8mm) | |
| VAC (V) | 250 | |

Connect with Littelfuse

Sign up to receive special offers and news

Enter your email

Submit

For more details about how we use your information, check our [Privacy Statement](#).

Mobile Site

- About Littelfuse
- About Littelfuse
 - Conflict Free Statement
 - History
 - Investor Relations
 - Legal
 - Press Room
 - Privacy Statement
 - Supply Chain Transparency
 - Website Feedback

- Explore Littelfuse
- Capabilities Brochures
 - Careers
 - Check Distributor Stock
 - Competitor Cross Reference
 - Industries
 - Order Samples
 - Products
 - Services

- Technical Resources
- Application Designs
 - Education
 - FAQs
 - iDesign™
 - Littelfuse University
 - Product Catalogs
 - Quality Documents
 - Technical Documents