5000 ppm Combustible Gas Detector

High Resolution Sensor <5S Quick Response Visual/Audible/Vibration Alarm







Fearless in the Dark

Effortlessly switch between day and night modes, with a built-in flashlight ensuring clear visibility in any condition.







Wide Application

GD-02 precisely detects gas leaks from trace to high volumes, ensuring safety in homes, factories, and labs.



Nine Advantages

Reasons For Your Choice





Connect to your computer for a quick firmware update—no mailing required, and it's much faster!



2" IPS Color Screen



Accurate Readings

Enjoy clear temperature and humidity readings on a 2.0-inch IPS screen with seamless unit switching.





PRODUCT PARAMETER

Parameter	Specification
Model Parameters	GD-02
Screen Material	2.0-inch Color Screen
Detectable Gases	Methane, Propane, Isobutane
Measurement Range	0~50000ppm (甲烷Methane)
	0~100 (A%LEL)
Resolution	1ppm/1%LEL
Measurement Range (%LEL)	0~100
Operating Temperature	-10~55°C
Warm-up Time	Around 15-16 seconds
Response Time(T90)	<5s
Recovery Time (T10)	<10s
Service Life	>3 years
Sampling Time	≈0.5s
Size	≈63×28×139(+360)mm
Product Weight	≈296g