

SENSITRON SEMICONDUCTOR

1N4460 thru 1N4496
1N4460US thru 1N4496US

TECHNICAL DATA DATA SHEET 5080, Rev B.2

1N44xx
*SJ44xx / *SX44xx / *SV44xx
*SS44xx

Zener 1.5W DIODE

- Ultra-low reverse leakage current
- Zener voltage available from 9.1V to 160V
- Sharp Zener knee
- Metallurgically bonded
- Hermetic, non-cavity glass package
- Lead finish SN63
- Operating Temperature: -65°C to +175°C.
- Storage Temperature: -65°C to +200°C.
- Power Dissipation: 1.5 Watts @ TA = 25oC

*Sensitron space equivalent diodes are manufactured and screened to MIL-PRF-19500 flow and guidelines starting from wafer fabrication through assembly and testing using our internal specification.

Electrical characteristics – Temperature 25°C unless otherwise noted


Part Number	Nominal Zener Voltage Vz	Test current I _{ZT}	Max Dynamic Impedance Z _{ZK} @ I _{ZK}	Max Knee Impedance I _{ZK} @ I _{ZK}		Max Continuous Current I _{ZM}	Max Surge Current I _{ZSM}	Maximum Reverse Current I _R @ V _R	
				Ω	mA			μA	V
1N4460/US	6.2	40	4	200	1	230	2.3	10	3.72
1N4461/US	6.8	37	2.5	200	1	210	2.1	5	4.08
1N4462/US	7.5	34	2.5	400	0.5	191	1.9	1	4.50
1N4463/US	8.2	31	3	400	0.5	174	1.7	.5	4.92
1N4464/US	9.1	28.0	4	500	0.5	157	1.6	.30	5.46
1N4465/US	10.0	25.0	5	500	.25	143	1.4	.30	8.00
1N4466/US	11.0	23.0	6	550	.25	130	1.3	.30	8.80
1N4467/US	12.0	21.0	7	550	.25	119	1.2	.20	9.60
1N4468/US	13.0	19.0	8	550	.25	110	1.1	.05	10.40
1N4469/US	15.0	17.0	9	600	.25	95	.95	.05	12.00
1N4470/US	16.0	15.5	10	600	.25	90	.90	.05	12.80
1N4471/US	18.0	14.0	11	650	.25	79	.79	.05	14.40
1N4472/US	20.0	12.5	12	650	.25	71	.71	.05	16.00
1N4473/US	22.0	11.5	14	650	.25	65	.65	.05	17.60
1N4474/US	24.0	10.5	16	700	.25	60	.60	.05	19.20
1N4475/US	27.0	9.5	18	700	.25	53	.53	.05	21.60
1N4476/US	30.0	8.5	20	750	.25	48	.48	.05	24.00
1N4477/US	33.0	7.5	25	800	.25	43	.43	.05	26.40
1N4478/US	36.0	7.0	27	850	.25	40	.40	.05	28.80
1N4479/US	39.0	6.5	30	900	.25	37	.37	.05	31.20
1N4480/US	43.0	6.0	40	950	.25	33	.33	.05	34.40
1N4481/US	47.0	5.5	50	1000	.25	30	.30	.05	37.60
1N4482/US	51.0	5.0	60	1100	.25	28	.28	.05	40.80
1N4483/US	56.0	4.5	70	1300	.25	26	.26	.25	44.80
1N4484/US	62.0	4.0	80	1500	.25	23	.23	.25	49.60
1N4485/US	68.0	3.7	100	1700	.25	21	.21	.25	54.40
1N4486/US	75.0	3.3	130	2000	.25	19	.19	.25	60.40
1N4487/US	82.0	3.0	160	2500	.25	17	.17	.25	65.60
1N4488/US	91.0	2.8	200	3000	.25	16	.16	.25	72.80
1N4489/US	100.0	2.5	250	3100	.25	14	.14	.25	80.00
1N4490/US	110.0	2.0	300	4000	.25	13	.13	.25	88.00
1N4491/US	120.0	2.0	400	4500	.25	12	.12	.25	96.00
1N4492/US	130.0	1.9	500	5000	.25	11	.11	.25	104.00
1N4493/US	150.0	1.7	700	6000	.25	9.5	.095	.25	120.00
1N4494/US	160.0	1.6	1000	6500	.25	8.9	.089	.25	128.00
1N4495/US	180.0	1.4	1300	7000	.25	7.9	.079	.25	144.00
1N4496/US	200.0	1.2	1500	8000	.25	7.2	.072	.25	160.00

* Dc TA=+150°C IR2

**1N4460 thru 1N4496
1N4460US thru 1N4496US**


SENSITRON

**TECHNICAL DATA
DATA SHEET 5080, Rev B.2**



1N4464 thru 1N4496

PACKAGE STYLE	DIMENSIONS - INCHES (MILLIMETERS)			
	ϕB	ϕD	G	L
Similar to DO-41	.028/.032 0.71/0.81	.060/.085 1.52/2.16	.106/.160 2.69/4.06	.80/1.30 20.32/33.02



1N4464US thru 1N4496US

PACKAGE STYLE	DIMENSIONS - INCHES (MILLIMETERS)			
	BL	BD	S	ECT
MELF	.168/.200 4.28/5.08	.091/.103 2.31/2.62	0.003 Min 0.008min	.019/.028 0.48/0.71

PART ORDERING INFORMATION:

The following part numbers can be purchased in either axial or surface mount devices and screened and tested to the military screening flow. The parts are marked in accordance with the testing performed, example:

Sensitron Screening Level	Part Number- Leaded Package (example for 1N4460)	Part Number- Surface Mount Package (example for 1N4460US)
SJ	SJ4460	SJ4460US
SX	SX4460	SX4460US
SV	SV4460	SV4460US
SS	SS4460	SS4460US

DISCLAIMER:

- 1- The information given herein, including the specifications and dimensions, is subject to change without prior notice to improve product characteristics. Before ordering, purchasers are advised to contact the Sensitron Semiconductor sales department for the latest version of the datasheet(s).
- 2- In cases where extremely high reliability is required (such as use in nuclear power control, aerospace and aviation, traffic equipment, medical equipment, and safety equipment), safety should be ensured by using semiconductor devices that feature assured safety or by means of users' fail-safe precautions or other arrangement.
- 3- In no event shall Sensitron Semiconductor be liable for any damages that may result from an accident or any other cause during operation of the user's units according to the datasheet(s). Sensitron Semiconductor assumes no responsibility for any intellectual property claims or any other problems that may result from applications of information, products or circuits described in the datasheets.
- 4- In no event shall Sensitron Semiconductor be liable for any failure in a semiconductor device or any secondary damage resulting from use at a value exceeding the absolute maximum rating.
- 5- No license is granted by the datasheet(s) under any patents or other rights of any third party or Sensitron Semiconductor.
- 6- The datasheet(s) may not be reproduced or duplicated, in any form, in whole or part, without the expressed written permission of Sensitron Semiconductor.
- 7- The products (technologies) described in the datasheet(s) are not to be provided to any party whose purpose in their application will hinder maintenance of international peace and safety nor are they to be applied to that purpose by their direct purchasers or any third party. When exporting these products (technologies), the necessary procedures are to be taken in accordance with related laws and regulations.