

Innovatively incorporates replaceable test board, easily tackling diverse test needs for unprecedented convenience and efficiency.



(Precise Decoding)
Under Your Contro

Supports NEC infrared signal decoding for easy remote testing, offering precise, efficient, and convenient user support.

ed Decodi

III LCR-P1



Mini & Portable

(Component Testing)

Inducto

<mark>Ultra Thin</mark>) Super Compact

Sleek, portable design for convenience and efficiency anywhere.





(Product Parameters

1.44 inches

300mAh lithium battery

USB Type-C, 5V/1A 71×87×28mm

Explanation

Forward voltage drop, junction capacitance, reverse leakage current.

1-2-3 Testing Area) Forward voltage rop, reverse breakdown voltage. K-A-A Testing Area) Reverse reakdown voltage.

Product Model Display Screen

Battery Capacity

Charging Specification

Product Size

Range

10<β<600

0.01-4.5V 0.01-32V

JFET

Category


Transistor

Diode

Applicable)

tegrates multiple detection functions to meet lifferent detection needs and is suitable for use in

nany occasions.



4 晶体管 TRANSISTO

Packing List

1. LCR-P1 host

2. Replaceable test board

4. User manual 6. Test hook*3 3. USB data cable 5. Packing box