

## LM120/LM320 Series 3-Terminal Negative Regulators

### General Description

The LM120 series are three-terminal negative regulators with a fixed output voltage of  $-5\text{V}$ ,  $-12\text{V}$ , and  $-15\text{V}$ , and up to  $1.5\text{A}$  load current capability. Where other voltages are required, the LM137 and LM137HV series provide an output voltage range of  $-1.2\text{V}$  to  $-47\text{V}$ .

The LM120 need only one external component—a compensation capacitor at the output, making them easy to apply. Worst case guarantees on output voltage deviation due to any combination of line, load or temperature variation assure satisfactory system operation.

Exceptional effort has been made to make the LM120 Series immune to overload conditions. The regulators have current limiting which is independent of temperature, combined with thermal overload protection. Internal current limiting protects against momentary faults while thermal shutdown prevents junction temperatures from exceeding safe limits during prolonged overloads.

Although primarily intended for fixed output voltage applications, the LM120 Series may be programmed for higher output voltages with a simple resistive divider. The low quiescent drain current of the devices allows this technique to be used with good regulation.



### Features

- Preset output voltage error less than  $\pm 3\%$
- Preset current limit
- Internal thermal shutdown
- Operates with input-output voltage differential down to  $1\text{V}$
- Excellent ripple rejection
- Low temperature drift
- Easily adjustable to higher output voltage

### LM120 Series Packages and Power Capability

| Device      | Package    | Rated Power Dissipation | Design Load Current |
|-------------|------------|-------------------------|---------------------|
| LM120/LM320 | TO-3 (K)   | 20W                     | 1.5A                |
|             | TO-39 (H)  | 2W                      | 0.5A                |
| LM320       | TO-220 (T) | 15W                     | 1.5A                |
| LM320M      | TO-202 (P) | 7.5W                    | 0.5A                |

### Typical Applications



—5 Volt Regulators (Note 3)

Absolute Maximum Ratings

If Military/Aerospace specified devices are required, please contact the National Semiconductor Sales Office/Distributors for availability and specifications. (Note 5)

Power Dissipation Internally Limited  
Input Voltage –25V

Input-Output Voltage Differential 25V  
Junction Temperatures See Note 1  
Storage Temperature Range –65°C to +150°C  
Lead Temperature (Soldering, 10 sec.) 300°C  
Plastic 260°C

Electrical Characteristics

| Order Numbers                                                                   |                                                                                                                             | Metal Can Package    |            |                      |       |                       |            |                       |              |                        |       | Power Plastic Package |            |              |
|---------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------|----------------------|------------|----------------------|-------|-----------------------|------------|-----------------------|--------------|------------------------|-------|-----------------------|------------|--------------|
|                                                                                 |                                                                                                                             | LM120K-5.0<br>(TO-3) |            | LM320K-5.0<br>(TO-3) |       | LM120H-5.0<br>(TO-39) |            | LM320H-5.0<br>(TO-39) |              | LM320T-5.0<br>(TO-220) |       |                       |            |              |
| Design Output Current (I <sub>O</sub> )<br>Device Dissipation (P <sub>D</sub> ) |                                                                                                                             | 1.5A<br>20W          |            | 1.5A<br>20W          |       | 0.5A<br>2W            |            | 0.5A<br>2W            |              | 1.5A<br>15W            |       | Units                 |            |              |
|                                                                                 |                                                                                                                             | Min                  | Typ        | Max                  | Min   | Typ                   | Max        | Min                   | Typ          | Max                    | Min   |                       | Typ        | Max          |
| Output Voltage                                                                  | T <sub>J</sub> = 25°C, V <sub>IN</sub> = 10V,<br>I <sub>LOAD</sub> = 5 mA                                                   | –5.1                 | –5         | –4.9                 | –5.2  | –5                    | –4.8       | –5.1                  | –5           | –4.9                   | –5.2  | –5                    | –4.8       | V            |
| Line Regulation                                                                 | T <sub>J</sub> = 25°C, I <sub>LOAD</sub> = 5 mA,<br>V <sub>MIN</sub> ≤ V <sub>IN</sub> ≤ V <sub>MAX</sub>                   |                      | 10         | 25                   |       | 10                    | 40         |                       | 10           | 25                     |       | 10                    | 40         | mV           |
| Input Voltage                                                                   |                                                                                                                             |                      | –25        | –7                   |       | –25                   | –7         |                       | –25          | –7                     |       | –25                   | –7.5       | V            |
| Ripple Rejection                                                                | f = 120 Hz                                                                                                                  |                      | 54         | 64                   |       | 54                    | 64         |                       | 54           | 64                     |       | 54                    | 64         | dB           |
| Load Regulation,<br>(Note 2)                                                    | T <sub>J</sub> = 25°C, V <sub>IN</sub> = 10V,<br>5 mA ≤ I <sub>LOAD</sub> ≤ I <sub>D</sub>                                  |                      | 50         | 75                   |       | 60                    | 100        |                       | 30           | 50                     |       | 50                    | 100        | mV           |
| Output Voltage,<br>(Note 1)                                                     | –7.5V ≤ V <sub>IN</sub> ≤ V <sub>MAX</sub> ,<br>5 mA ≤ I <sub>LOAD</sub> ≤ I <sub>D</sub> , P ≤ P <sub>D</sub>              | –5.20                |            | –4.80                | –5.25 |                       | –4.75      | –5.20                 |              | –4.80                  | –5.25 |                       | –4.75      | V            |
| Quiescent Current                                                               | V <sub>MIN</sub> ≤ V <sub>IN</sub> ≤ V <sub>MAX</sub>                                                                       |                      | 1          | 2                    |       | 1                     | 2          |                       | 1            | 2                      |       | 1                     |            | mA           |
| Quiescent Current<br>Change                                                     | T <sub>J</sub> = 25°C<br>V <sub>MIN</sub> ≤ V <sub>IN</sub> ≤ V <sub>MAX</sub><br>5 mA ≤ I <sub>LOAD</sub> ≤ I <sub>D</sub> |                      | 0.1<br>0.1 | 0.4<br>0.4           |       | 0.1<br>0.1            | 0.4<br>0.4 |                       | 0.05<br>0.04 | 0.4<br>0.4             |       | 0.1<br>0.1            | 0.4<br>0.4 | mA           |
| Output Noise Voltage                                                            | T <sub>A</sub> = 25°C, C <sub>L</sub> = 1 μF, I <sub>L</sub> = 5 mA,<br>V <sub>IN</sub> = 10V, 10 Hz ≤ f ≤ 100 kHz          |                      | 150        |                      |       | 150                   |            |                       | 150          |                        |       | 150                   |            | μV           |
| Long Term Stability                                                             |                                                                                                                             |                      | 5          | 50                   |       | 5                     | 50         |                       | 5            | 50                     |       | 10                    |            | mV           |
| Thermal Resistance<br>Junction to Case<br>Junction to Ambient                   |                                                                                                                             |                      | 3<br>35    |                      |       |                       | 3<br>35    | Note 4<br>Note 4      |              | Note 4<br>Note 4       |       | 4<br>50               |            | °C/W<br>°C/W |

**Note 1:** This specification applies over –55°C ≤ T<sub>J</sub> ≤ +150°C for the LM120 and 0°C ≤ T<sub>J</sub> ≤ +125°C for the LM320.  
**Note 2:** Regulation is measured at constant junction temperature. Changes in output voltage due to heating effects must be taken into account separately. To ensure constant junction temperature, low duty cycle, pulse testing is used. The LM120/LM320 series does have low thermal feedback, improving line and load regulation. On all other tests, even though power dissipation is internally limited, electrical specifications apply only up to P<sub>D</sub>.  
**Note 3:** For –5V 3 amp regulators, see LM145 data sheet.  
**Note 4:** Thermal resistance of typically 85°C/W (in 400 linear feet air flow), 224°C/W (in static air) junction to ambient, of typically 21°C/W junction to case.  
**Note 5:** Refer to RETS120-5H drawing for LM120H-5.0 or RETS120-5K drawing for LM120-5K military specifications.

## — 12 Volt Regulators

### Absolute Maximum Ratings

If Military/Aerospace specified devices are required, please contact the National Semiconductor Sales Office/Distributors for availability and specifications. (Note 4)

Power Dissipation

Internally Limited

Input Voltage

–35V

Input-Output Voltage Differential

30V

Junction Temperatures

See Note 1

Storage Temperature Range

–65°C to +150°C

Lead Temperature (Soldering, 10 sec.)

300°C

### Electrical Characteristics

| Order Numbers                                                                   |                                                                                                                             | Metal Can Package   |     |           |                     |            |       |                      |      |            |                      |            |        | Power Plastic Package |     |       | Units |
|---------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------|---------------------|-----|-----------|---------------------|------------|-------|----------------------|------|------------|----------------------|------------|--------|-----------------------|-----|-------|-------|
|                                                                                 |                                                                                                                             | LM120K-12<br>(TO-3) |     |           | LM320K-12<br>(TO-3) |            |       | LM120H-12<br>(TO-39) |      |            | LM320H-12<br>(TO-39) |            |        | LM320T-12<br>(TO-220) |     |       |       |
| Design Output Current (I <sub>D</sub> )<br>Device Dissipation (P <sub>D</sub> ) |                                                                                                                             | 1A<br>20W           |     | 1A<br>20W |                     | 0.2A<br>2W |       | 0.2A<br>2W           |      | 0.2A<br>2W |                      | 0.2A<br>2W |        | 1A<br>15W             |     |       |       |
| Parameter                                                                       | Conditions (Note 1)                                                                                                         | Min                 | Typ | Max       | Min                 | Typ        | Max   | Min                  | Typ  | Max        | Min                  | Typ        | Max    | Min                   | Typ | Max   |       |
| Output Voltage                                                                  | T <sub>J</sub> = 25°C, V <sub>IN</sub> = 17V,<br>I <sub>LOAD</sub> = 5 mA                                                   | −12.3               | −12 | −11.7     | −12.4               | −12        | −11.6 | −12.3                | −12  | −11.7      | −12.4                | −12        | −11.6  | −12.4                 | −12 | −11.6 |       |
| Line Regulation                                                                 | T <sub>J</sub> = 25°C, I <sub>LOAD</sub> = 5 mA,<br>V <sub>MIN</sub> ≤ V <sub>IN</sub> ≤ V <sub>MAX</sub>                   |                     | 4   | 10        |                     | 4          | 20    |                      | 4    | 10         |                      | 4          | 20     |                       | 4   | 20    |       |
| Input Voltage                                                                   |                                                                                                                             | −32                 |     | −14       | −32                 |            | −14   | −32                  |      | −14        | −32                  |            | −14    | −32                   |     | −14.5 |       |
| Ripple Rejection                                                                | f = 120 Hz                                                                                                                  | 56                  | 80  |           | 56                  | 80         |       | 56                   | 80   |            | 56                   | 80         |        | 56                    | 80  |       |       |
| Load Regulation,<br>(Note 2)                                                    | T <sub>J</sub> = 25°C, V <sub>IN</sub> = 17V,<br>5 mA ≤ I <sub>LOAD</sub> ≤ I <sub>D</sub>                                  |                     | 30  | 80        |                     | 30         | 80    |                      | 10   | 25         |                      | 10         | 40     |                       | 30  | 80    |       |
| Output Voltage,<br>(Note 1)                                                     | 14.5V ≤ V <sub>IN</sub> ≤ V <sub>MAX</sub> ;<br>5 mA ≤ I <sub>LOAD</sub> ≤ I <sub>D</sub> , P ≤ P <sub>D</sub>              | −12.5               |     | −11.5     | −12.6               |            | −11.4 | −12.5                |      | −11.5      | −12.6                |            | −11.4  | −12.6                 |     | −11.4 |       |
| Quiescent Current                                                               | V <sub>MIN</sub> ≤ V <sub>IN</sub> ≤ V <sub>MAX</sub>                                                                       |                     | 2   | 4         |                     | 2          | 4     |                      | 2    | 4          |                      | 2          | 4      |                       | 2   | 4     |       |
| Quiescent Current<br>Change                                                     | T <sub>J</sub> = 25°C<br>V <sub>MIN</sub> ≤ V <sub>IN</sub> ≤ V <sub>MAX</sub><br>5 mA ≤ I <sub>LOAD</sub> ≤ I <sub>D</sub> |                     | 0.1 | 0.4       |                     | 0.1        | 0.4   |                      | 0.05 | 0.4        |                      | 0.05       | 0.4    |                       | 0.1 | 0.4   |       |
| Output Noise Voltage                                                            | T <sub>A</sub> = 25°C, C <sub>L</sub> = 1 μF, I <sub>L</sub> = 5 mA,<br>V <sub>IN</sub> = 17V, 10 Hz ≤ f ≤ 100 kHz          |                     | 400 |           |                     | 400        |       |                      | 400  |            |                      | 400        |        |                       | 400 |       |       |
| Long Term Stability                                                             |                                                                                                                             |                     | 12  | 120       |                     | 12         | 120   |                      | 12   | 120        |                      | 12         | 120    |                       | 24  |       |       |
| Thermal Resistance<br>Junction to Case                                          |                                                                                                                             |                     |     | 3         |                     |            | 3     |                      |      | Note 3     |                      |            | Note 3 |                       | 4   |       |       |
| Junction to Ambient                                                             |                                                                                                                             |                     |     | 35        |                     |            | 35    |                      |      | Note 3     |                      |            | Note 3 |                       | 50  |       |       |

**Note 1:** This specification applies over –55°C ≤ T<sub>J</sub> ≤ +150°C for the LM120 and 0°C ≤ T<sub>J</sub> ≤ +125°C for the LM320.

**Note 2:** Regulation is measured at constant junction temperature. Changes in output voltage due to heating effects must be taken into account separately. To ensure constant junction temperature, low duty cycle, pulse testing is used. The LM120/LM320 series does have low thermal feedback, improving line and load regulation. On all other tests, even though power dissipation is internally limited, electrical specifications apply only up to P<sub>D</sub>.

**Note 3:** Thermal resistance of typically 85°C/W (in 400 linear feet/min air flow), 224°C/W (in static air) junction to ambient, of typically 21°C/W junction to case.

**Note 4:** Refer to RETS120H-12 drawing for LM120H-12 or RETS120-12K drawing for LM120K-12 military specifications.

## — 15 Volt Regulators

### Absolute Maximum Ratings

If Military/Aerospace specified devices are required, please contact the National Semiconductor Sales Office/Distributors for availability and specifications. (Note 4)

Power Dissipation

Input Voltage

LM120/LM320

LM320T

Internally Limited

—40V

—35V

Input-Output Voltage Differential

Junction Temperatures

Storage Temperature Range

Lead Temperature (Soldering, 10 sec.)

30V

See Note 1

—65°C to +150°C

300°C

### Electrical Characteristics

| Order Numbers                          |                                                                                                                             | Metal Can Package   |     |                     |       |                      |       |                      |      |                       |       |           |        | Power Plastic Package |     |       |      | Units |
|----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------|---------------------|-----|---------------------|-------|----------------------|-------|----------------------|------|-----------------------|-------|-----------|--------|-----------------------|-----|-------|------|-------|
|                                        |                                                                                                                             | LM120K-15<br>(TO-3) |     | LM320K-15<br>(TO-3) |       | LM120H-15<br>(TO-39) |       | LM320H-15<br>(TO-39) |      | LM320T-15<br>(TO-220) |       |           |        |                       |     |       |      |       |
|                                        |                                                                                                                             | 1A<br>20W           |     | 1A<br>20W           |       | 0.2A<br>2W           |       | 0.2A<br>2W           |      | 1A<br>15W             |       | 1A<br>15W |        |                       |     |       |      |       |
| Parameter                              | Conditions (Note 1)                                                                                                         | Min                 | Typ | Max                 | Min   | Typ                  | Max   | Min                  | Typ  | Max                   | Min   | Typ       | Max    | Min                   | Typ | Max   |      |       |
| Output Voltage                         | T <sub>J</sub> = 25°C, V <sub>IN</sub> = 20V,<br>I <sub>LOAD</sub> = 5 mA                                                   | −15.3               | −15 | −14.7               | −15.4 | −15                  | −14.6 | −15.3                | −15  | −14.7                 | −15.4 | −15       | −14.6  | −15.5                 | −15 | −14.5 | V    |       |
| Line Regulation                        | T <sub>J</sub> = 25°C, I <sub>LOAD</sub> = 5 mA,<br>V <sub>MIN</sub> ≤ V <sub>IN</sub> ≤ V <sub>MAX</sub>                   |                     | 5   | 10                  |       | 5                    | 20    |                      | 5    | 10                    |       | 5         | 20     |                       | 5   | 20    | mV   |       |
| Input Voltage                          |                                                                                                                             | −35                 |     | −17                 | −35   |                      | −17   | −35                  |      | −17                   | −35   |           | −17    | −35                   |     | −17.5 | V    |       |
| Ripple Rejection                       | f = 120 Hz                                                                                                                  | 56                  | 80  |                     | 56    | 80                   |       | 56                   | 80   |                       | 56    | 80        |        | 56                    | 80  |       | dB   |       |
| Load Regulation,<br>(Note 2)           | T <sub>J</sub> = 25°C, V <sub>IN</sub> = 20V,<br>5 mA ≤ I <sub>LOAD</sub> ≤ I <sub>O</sub>                                  |                     | 30  | 80                  |       | 30                   | 80    |                      | 10   | 25                    |       | 10        | 40     |                       | 30  | 80    | mV   |       |
| Output Voltage,<br>(Note 1)            | 17.5V ≤ V <sub>IN</sub> ≤ V <sub>MAX</sub> ,<br>5 mA ≤ I <sub>LOAD</sub> ≤ I <sub>O</sub> , P ≤ P <sub>D</sub>              | −15.5               |     | −14.5               | −15.6 |                      | −14.4 | −15.5                |      | −14.5                 | −15.6 |           | −14.4  | −15.7                 |     | −14.3 | V    |       |
| Quiescent Current                      | V <sub>MIN</sub> ≤ V <sub>IN</sub> ≤ V <sub>MAX</sub>                                                                       |                     | 2   | 4                   |       | 2                    | 4     |                      | 2    | 4                     |       | 2         | 4      |                       | 2   | 4     | mA   |       |
| Quiescent Current<br>Change            | T <sub>J</sub> = 25°C<br>V <sub>MIN</sub> ≤ V <sub>IN</sub> ≤ V <sub>MAX</sub><br>5 mA ≤ I <sub>LOAD</sub> ≤ I <sub>O</sub> |                     | 0.1 | 0.4                 |       | 0.1                  | 0.4   |                      | 0.05 | 0.4                   |       | 0.05      | 0.4    |                       | 0.1 | 0.4   | mA   |       |
| Output Noise Voltage                   | T <sub>A</sub> = 25°C, C <sub>L</sub> = 1 μF, I <sub>L</sub> = 5 mA,<br>V <sub>IN</sub> = 20V, 10 Hz ≤ f ≤ 100 kHz          |                     | 400 |                     |       | 400                  |       |                      | 400  |                       |       | 400       |        |                       | 400 |       | μV   |       |
| Long Term Stability                    |                                                                                                                             |                     | 15  | 150                 |       | 15                   | 150   |                      | 15   | 150                   |       | 15        | 150    |                       | 30  |       | mV   |       |
| Thermal Resistance<br>Junction to Case |                                                                                                                             |                     |     | 3                   |       |                      | 3     |                      |      | Note 3                |       |           | Note 3 |                       | 4   |       | °C/W |       |
| Junction to Ambient                    |                                                                                                                             |                     |     | 35                  |       |                      | 35    |                      |      | Note 3                |       |           | Note 3 |                       | 50  |       | °C/W |       |










**Note 1:** This specification applies over —55°C ≤ T<sub>J</sub> ≤ +150°C for the LM120 and 0°C ≤ T<sub>J</sub> ≤ +125°C for the LM320.

**Note 2:** Regulation is measured at constant junction temperature. Changes in output voltage due to heating effects must be taken into account separately. To ensure constant junction temperature, low duty cycle, pulse testing is used. The LM120/LM320 series does have low thermal feedback, improving line and load regulation. On all other tests, even though power dissipation is internally limited, electrical specifications apply only up to P<sub>D</sub>.

**Note 3:** Thermal resistance of typically 85°C/W (in 400 linear feet/min air flow), 224°C/W (in static air) junction to ambient, of typically 21°C/W junction to case.

**Note 4:** Refer to RETS120-15H drawing for LM120H-15 or RETS120-15K drawing for LM120K-15 military specifications.





## Typical Performance Characteristics



\*These curves for LM120.  
Derate 25°C further for LM320.

TL/H/7767-4


## Typical Performance Characteristics (Continued)



TL/H/7767-5

## Typical Applications (Continued)

### High Stability 1 Amp Regulator



TL/H/7767-6

Lead and line regulation — 0.01% temperature stability — 0.2%

†Determines Zener current.


††Solid tantalum.

An LM120-12 or LM120-15 may be used to permit higher input voltages, but the regulated output voltage must be at least  $-15V$  when using the LM120-12 and  $-18V$  for the LM120-15.

\*\*Select resistors to set output voltage. 2 ppm/°C tracking suggested.

## Typical Applications (Continued)

### Wide Range Tracking Regulator




TL/H/7767-7

\*Resistor tolerance of R1 and R2 determine matching of (+) and (-) inputs.

\*\*Necessary only if raw supply capacitors are more than 3" from regulators. An LM3086N array may substitute for Q1, D1 and D2 for better stability and tracking. In the array diode transistors Q5 and Q4 (in parallel) make up D2; similarly, Q1 and Q2 become D1 and Q3 replaces the 2N2222.

### Variable Output



TL/H/7767-9


\*Optional. Improves transient response and ripple rejection.

$$V_{OUT} = V_{SET} \frac{R1 + R2}{R2}$$

SELECT R2 AS FOLLOWS:

LM120-5 — 300Ω  
LM120-12 — 750Ω  
LM120-15 — 1k


### Current Source



$$I_{OUT} = 1 \text{ mA} + \frac{5.0V}{R1}$$

TL/H/7767-8

### ± 15V, 1 Amp Tracking Regulators



TL/H/7767-12


### Performance (Typical)

Load Regulation at  $\Delta I_L = 1A$  10 mV 1 mV  
Output Ripple,  $C_{IN} = 3000 \mu F$ ,  $I_L = 1A$  100  $\mu V_{rms}$  100  $\mu V_{rms}$   
Temperature Stability +50 mV +50 mV  
Output Noise 10 Hz  $\leq f \leq 10$  kHz 150  $\mu V_{rms}$  150  $\mu V_{rms}$

\*Resistor tolerance of R4 and R5 determine matching of (+) and (-) outputs.

\*\*Necessary only if raw supply filter capacitors are more than 2" from regulators.


### Light Controllers Using Silicon Photo Cells



TL/H/7767-10

\*Lamp brightness increases until  $i_L = 5V/R1$  ( $i_L$  can be set as low as 1  $\mu A$ ).

†Necessary only if raw supply filter capacitor is more than 2" from LM320MP.




TL/H/7767-11

\*Lamp brightness increases until  $i_L = i_Q$  (1 mA) + 5V/R1.

†Necessary only if raw supply filter capacitor is more than 2" from LM320.


## Connection Diagrams



Bottom View

TL/H/7767-13


**Metal Can Package TO-39 (H)**  
 Order Number LM120H-5.0, LM120H-12, LM120H-15,  
 LM120H-5.0/883, LM120H-12/883, LM120H-15/883,  
 LM320H-5.0, LM320H-12 or LM320H-15  
 See NS Package Number H03A



Bottom View

TL/H/7767-14

**Steel Metal Can Package TO-3 (K)**  
 Order Number LM120K-5.0/883, LM120K-12/883,  
 LM120K-15/883, LM320K-5.0, LM320K-12 or LM320K-15  
 See NS Package Number K02A




Front View

TL/H/7767-17

**Power Package TO-220 (T)**  
 Order Number LM320T-5.0, LM320T-12 or LM320T-15  
 See NS Package Number T03B


## Schematic Diagrams



TL/H/7767-18



## Schematic Diagrams (Continued)

–12V and –15V



TL/H/7767-19

## Physical Dimensions inches (millimeters)




H03A (REV B)

**Metal Can Package (TO-39) (H)**

**Order Number LM120H-5.0, LM120H-12, LM120H-15, LM320H-5.0, LM320H-12 or LM320H-15**  
**NS Package Number H03A**


[illegible]

10

**Physical Dimensions** inches (millimeters) (Continued)

P03A (REV F)

**Power Package TO-202 (P)**  
**Order Number LM320MP-5.0, LM320MP-12 or LM320MP-15**  
**NS Package Number P03A**

**Physical Dimensions** inches (millimeters) (Continued)

**Power Package TO-220 (T)**  
**Order Number LM320T-5.0, LM320T-12 or LM320T-15**  
**NS Package Number T03B**

T03B (REV L)