

PRODUCTS

SHOP

LEARN

DOCS

LIBSTOCK





Compilers Development Boards Click Boards Debuggers Smart Displays Software Tools Add-On Boards Special




SHT click

PID: MIKROE-2101

Weight: 23 g

SHT click is a temperature and humidity sensing click board that carries
Sensiron's SHT3x-DIS IC. Compared to its predecessor (SHT11), SHT3x click has increased reliability and enhanced signal processing features with a high signal-to-noise ratio.





DESCRIPTION

SPECIFICATION

TUTORIALS

REVIEWS

Table of contents

1. Downloads

SHT click is a temperature and humidity sensing click board that carries Sensiron's SHT3x-DIS IC. Compared to its predecessor (SHT11), SHT3x click has increased reliability and enhanced signal processing features with a high signal-to-noise ratio. Best measurement results are achieved within a 5-60° C temperature range (0.015 resolution) and a 20%–80%RH humidity range (0.01 resolution). SHT click outputs a fully calibrated, linearized, and temperature compensated digital output through the mikroBUSTM I2C interface (SCL, SDA). An additional INT pin is for setting up alerts for certain temperature or humidity values. Finally, a RST pin allows you to reset the sensor. Designed to use either 3.3V or 5V power supply.

Downloads



SHT click examples 🔀



SHT click Documentation 🔀

PRODUCTS IN THE SAME CATEGORY











SHT1x click

Add to cart

LightHz click
.90

add to cart

Accel click

.00

add to cart

THERMO click

.00

ਜ਼ Add to cart

IrThermo click 5V

.00

Add to cart

