

NTE3065

0.300 Inch, Polarity and Overflow, Numeric Display, Common Anode

Features:

- Fast switching – excellent for multiplexing
- Low power consumption
- Bold solid segments that are highly legible
- Solid state reliability – long operation life
- Impact resistant plastic construction
- Directly compatible with integrated circuits
- High brightness with high contrast
- Standard 14 pin dual-in-line package
- Wide angle view 150°

Absolute Raximum Ratings:

Power Dissipation at +25°C ambient	300mW
Derate linearly from +50°C	–4.29mW/°C
Continuous Forward Current	
Total	150mA
Per Segment	30mA
Decimial Point	30mA
Reverse Voltage	
Per Segment	6V
Decimal Point	6V
Solsderring Time at 260°C (Note 1,2)	5 sec.
Operating Temperature Range	–40° to +85°C
Storage Temperature Range	–40° to +85°C

Note 1. Leads of the device immersed to 1/16 inch from the body. Maximum device surface temperature is 140°C.

Note 2. For flux removal, Freon TF, Freon TE, Isoproponal or water may be used up to their boiling points.

Operating Characteristics: ($T_A = +25^{\circ}\text{C}$ unless otherwise specified)

Parameter	Test Conditions	Min	Typ	Max	Unit
Luminous Intensity, Digit Average	$I_F = 10\text{mA}$ (Note 3,4)	125	350	–	μcd
Peak Emission Wavelength		–	660	–	nm
Spectral Line Half Width		–	20	–	nm
Forward Voltage Segment	$I_F = 20\text{mA}$	–	–	2.0	V
Decimal Point		–	–	2.0	V
Dynamic Resistance Segment	$I_{pk} = 100\text{mA}$	–	2	–	Ω
Decimal Point		–	2	–	Ω
Capacitance Segment	$V = 0$	–	35	80	pF
Decimal Point		–	35	80	pF
Reverse Current Segment	$V_R = 5.0\text{V}$	–	–	100	μA
Decimal Point		–	–	100	μA

Note 3. The digit average Luminous Intensity is obtained by summing the Luminous Intensity of each segment and dividing by the total number of segments. Intensity will not vary more than $\pm 33\%$ between all segments within a digit.

Note 4. The decimal point is designed to have the same surface brightness as the segments, therefore, the Luminous Intensity of the decimal point is .3 times the Luminous Intensity of the segments, since the area of the decimal point is .3 times the area of the average points.

Pin Connection Diagram

