



NTE3322

Insulated Gate Bipolar Transistor N-Channel Enhancement Mode, High Speed Switch

Features:

- High Input Impedance
- High Speed
- Low Saturation Voltage
- Enhancement Mode

Applications:




- High Power Switching

Absolute Maximum Ratings: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Collector-Emitter Voltage, V_{CES}	900V
Gate-Emitter Voltage, V_{GES}	$\pm 25\text{V}$
Collector Current, I_C	
DC	60A
Pulse (1ms)	120A
Collector Power Dissipation ($T_C = +25^\circ\text{C}$), P_C	200W
Operating Junction Temperature, T_J	$+150^\circ\text{C}$
Storage Temperature Range, T_{stg}	-55°C to $+150^\circ\text{C}$
Thermal Resistance, Junction-to-Case, R_{thJC}	0.625°C/W
Screw Torque	0.8Nm

Electrical Characteristics: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Gate Leakage Current	I_{GES}	$V_{GE} = \pm 25\text{V}$, $V_{CE} = 0$	—	—	± 500	nA
Collector Cutoff Current	I_{CES}	$V_{CE} = 900\text{V}$, $V_{GE} = 0$	—	—	1.0	mA
Collector-Emitter Breakdown Voltage	$V_{(BR)CES}$	$I_C = 2\text{mA}$, $V_{GE} = 0$	900	—	—	V
Gate-Emitter Cutoff Voltage	$V_{GE(off)}$	$I_C = 60\text{mA}$, $V_{CE} = 5\text{V}$	3.0	—	6.0	V
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = 10\text{A}$, $V_{GE} = 15\text{V}$	—	—	2.4	V
		$I_C = 60\text{A}$, $V_{GE} = 15\text{V}$	—	2.4	3.7	V
Input Capacitance	C_{ies}	$V_{CE} = 10\text{V}$, $V_{GE} = 0$, $f = 1\text{MHz}$	—	5300	—	pF
Rise Time	t_r	$V_{CC} = 600\text{V}$	—	0.25	0.60	μs
Turn-On Time	t_{on}		—	0.35	0.80	μs
Fall Time	t_f		—	0.25	0.40	μs
Turn-Off Time	t_{off}		—	0.50	1.00	μs



Note: Collector connected to heat sink.