



Okystar Technology Co., Ltd.

Tel: 0086-755-23878860 Web: [www.okystar.com](http://www.okystar.com) [www.okynewstar.en.alibaba.com](http://www.okynewstar.en.alibaba.com)

Add: Room1105, Block B, ChinTo Technology Building, Minzhi Road, LongHua, Shenzhen,China

---



**SKU:**OKY3399-10A

**Name:**5V2A 1A Micro USB single charging port input dual USB output 18650 lithium battery digital display charging module

**Description:**

- 1.5V2A 1A Micro USB single charging port input dual USB output 18650 lithium battery digital display charging module
- 2.Portable Mobile Power Supply Module
- 3.Supports 2 USB cables

**Specification:**

- 1.Input Voltage B+ to B-:3.0~4.2V
- 2.Overcharge Detection voltage: $4.20 \pm 0.05V$
- 3.Overcharge Release voltage: $4.100 \pm 0.05V$
- 4.Overcharge Detection delay time:<200 ms
- 5.Over discharge Detection voltage: $3.0 \pm 0.1V$
- 6.Over discharge Release voltage: $3.100 \pm 0.1V$
- 7.Over discharge Detection delay time:<100 ms
- 8.Output constant current:2A
- 9.Short detection delay time:<50uS
- 10.Short circuit protection Release Conditions:Cut off load
- 11.Normal current consumption of PCM:Max 60uA
- 12.Stan by current consumption:Max 50uA
- 13.Allowed 0V change:YES
- 14.Max continuous charge/discharge current:1.5/2A
- 15.Suggest working temperature:-5~45°C
- 16.IR of PCM: $\leq 65m \Omega$
- 17.Charge voltage:4.5~5.5V
- 18.Application:For steam education
- 19.Weight:27g

**Package Including:**

- 1 \* Battery charger module