





Raspberry Pi 4 Model B

Published April 2026



The terms HDMI, HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

Overview



Raspberry Pi 4 Model B features a high-performance 64-bit quad-core processor, dual-display support at resolutions up to 4K via a pair of micro HDMI ports, hardware video decode at up to 4Kp60, up to 8GB of RAM, dual-band 2.4/5.0 GHz wireless LAN, Bluetooth 5.0, Gigabit Ethernet, USB 3.0, and PoE capability (via a separate PoE HAT add-on). For the end user, Raspberry Pi 4 Model B provides desktop performance comparable to entry-level x86 PC systems.

This product retains backwards compatibility with the prior-generation Raspberry Pi 3 Model B+ and has similar power consumption, while offering substantial increases in processor speed, multimedia performance, memory, and connectivity.

The dual-band wireless LAN and Bluetooth have modular compliance certification, allowing the board to be designed into end products with significantly reduced compliance testing, improving both cost and time to market.

Specification

Processor:	Broadcom BCM2711, quad-core Cortex-A72 (ARM v8) 64-bit SoC @ 1.8GHz
Memory:	1GB, 2GB, 3GB, 4GB or 8GB LPDDR4 (depending on model) with on-die ECC
Connectivity:	• 2.4 GHz and 5.0 GHz IEEE 802.11b/g/n/ac wireless LAN, Bluetooth 5.0, BLE • Gigabit Ethernet • 2 × USB 3.0 ports • 2 × USB 2.0 ports.
GPIO:	Standard 40-pin GPIO header (fully backwards-compatible with previous boards)
Video & sound:	• 2 × micro HDMI ports (up to 4Kp60 supported) • 2-lane MIPI DSI display port • 2-lane MIPI CSI camera port • 4-pole stereo audio and composite video port
Multimedia:	H.265 (4Kp60 decode); H.264 (1080p60 decode, 1080p30 encode); OpenGL ES, 3.0 graphics
SD card support:	Micro SD card slot for loading operating system and data storage
Input power:	• 5V DC via USB-C connector (minimum 3A¹) • 5V DC via GPIO header (minimum 3A¹) • Power over Ethernet (PoE)–enabled (requires separate PoE HAT)
Environment:	Operating temperature 0–50°C


MTBF¹ Ground Benign: 211 000 hours

Production lifetime: Raspberry Pi 4 Model B will remain in production until at least January 2034.

Compliance: For a full list of local and regional product approvals, please visit pip.raspberrypi.com

¹ Mean Time Between Failure

Physical specification



Note:

All dimensions in mm

All dimensions are approximate and for reference purposes only. The dimensions shown should not be used for producing production data

The dimensions are subject to part and manufacturing tolerances

Not all of the board components are shown. Please reference a physical board for representation of componentry

Dimensions may be subject to change

WARNINGS


- This product should only be connected to an external power supply rated at 5V/3A DC or 5.1V/ 3A DC minimum¹. Any external power supply used with Raspberry Pi 4 Model B shall comply with relevant regulations and standards applicable in the country of intended use.
- This product should be operated in a well-ventilated environment and, if used inside a case, the case should not be covered.
- This product should be placed on a stable, flat, non-conductive surface in use and should not be contacted by conductive items.
- The connection of incompatible devices to the GPIO connection may affect compliance and result in damage to the unit and invalidate the warranty.
- All peripherals used with this product should comply with relevant standards for the country of use and be marked accordingly to ensure that safety and performance requirements are met. These articles include but are not limited to keyboards, monitors and mice when used in conjunction with Raspberry Pi.
- Where peripherals are connected that do not include the cable or connector, the cable or connector must offer adequate insulation and operation in order that the relevant performance and safety requirements are met.

SAFETY INSTRUCTIONS

To avoid malfunction or damage to this product please observe the following:

- Do not expose to water, moisture or place on a conductive surface whilst in operation.
- Do not expose it to heat from any source; Raspberry Pi 4 Model B is designed for reliable operation at normal ambient room temperatures.
- Take care whilst handling to avoid mechanical or electrical damage to the printed circuit board and connectors.
- Avoid handling the printed circuit board whilst it is powered and only handle by the edges to minimise the risk of electrostatic discharge damage.

¹ A good quality 2.5A power supply can be used if downstream USB peripherals consume less than 500mA in total.






Raspberry Pi is a trademark of Raspberry Pi Ltd

RASPBERRY PI 4

La **Raspberry Pi 4 Model B** es una computadora de placa única que ofrece una plataforma compacta y versátil para desarrollar una amplia variedad de proyectos. Su capacidad de procesamiento, conectividad y compatibilidad con diferentes accesorios permiten utilizarla en aplicaciones de programación, automatización, IoT, educación y desarrollo de sistemas.




¿ CUÁL ES LA DIFERENCIA ENTRE LOS MODELOS RASPBERRY PI?

	Raspberry Pi Zero W	Raspberry Pi 3	Raspberry Pi 4	Raspberry Pi 5
Procesador	BCM2835 Single-Core	BCM2837B0 Cortex-A53 1.4 GHz	Quad-Core Cortex-A72 1.5 GHz	Quad-Core Cortex-A76 2.4 GHz
RAM	512 MB	1 GB y 512 MB	1GB, 2 GB, 3 GB, 4 GB y 8 GB	2 GB, 4 GB, 8 GB y 16 GB
Conectividad	Wi-Fi Bluetooth 4.1	Wi-Fi Bluetooth 4.2 Ethernet	Wi-Fi Bluetooth 5.0 Ethernet	Wi-Fi Bluetooth 5.0 Ethernet
Puertos	1 x micro USB	4 x USB 2.0	2 x USB 2.0 2 x USB 3.0	2 x USB 2.0 2 x USB 3.0
Salida de video	1 x mini HDMI (Hasta 1080p)	1 x HDMI (Hasta 4K)	2 x micro HDMI (Hasta 4K)	2 x micro HDMI (Hasta 4K)

¿CUÁL RASPBERRY PI ELEGIR?

RASPBERRY PI 5

Ideal para visión artificial, inteligencia artificial, automatización avanzada, servidores y robótica.



RASPBERRY PI 4

Ideal para IoT, servidores, automatización, kioscos, multimedia, programación, sistemas industriales.

RASPBERRY PI ZERO W

Ideal para IoT compacto, uso de sensores y cámaras, automatización básica y proyectos embebidos.

RASPBERRY PI 3

Ideal para IoT, domótica, gateways, control, proyectos educativos y servidores ligeros.

Por su flexibilidad, la **Raspberry Pi 4** puede integrarse en proyectos como servidores, sistemas de monitoreo, centros multimedia, soluciones de domótica y aplicaciones de control. Además, su amplio ecosistema de software, módulos y accesorios facilita la creación de **Raspberry Pi proyectos** tanto para aprendizaje como para soluciones personalizadas.