



Order this document by TL062/D

**TL062  
TL064**

**Low Power JFET Input  
Operational Amplifiers**




These JFET input operational amplifiers are designed for low power applications. They feature high input impedance, low input bias current and low input offset current. Advanced design techniques allow for higher slew rates, gain bandwidth products and output swing.

The commercial and vehicular devices are available in Plastic dual in-line and SOIC packages.

- Low Supply Current: 200  $\mu$ A/Amplifier
- Low Input Bias Current: 5.0 pA
- High Gain Bandwidth: 2.0 MHz
- High Slew Rate: 6.0 V/ $\mu$ s
- High Input Impedance:  $10^{12} \Omega$
- Large Output Voltage Swing:  $\pm 14$  V
- Output Short Circuit Protection

**LOW POWER JFET INPUT  
OPERATIONAL AMPLIFIERS**

**SEMICONDUCTOR  
TECHNICAL DATA**



**ORDERING INFORMATION**

Op Amp Function	Device	Operating Temperature Range	Package
Dual	TL062CD, ACD	$T_A = 0^\circ$ to $+70^\circ$ C	SO-8
	TL062CP, ACP		Plastic DIP
Dual	TL062VD	$T_A = -40^\circ$ to $+85^\circ$ C	SO-8
	TL062VP		Plastic DIP
Quad	TL064CD, ACD	$T_A = 0^\circ$ to $+70^\circ$ C	SO-14
	TL064CN, ACN		Plastic DIP
Quad	TL064VD	$T_A = -40^\circ$ to $+85^\circ$ C	SO-14
	TL064VN		Plastic DIP

© Motorola, Inc. 1996

Rev 5

## TL062 TL064

## MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Supply Voltage (from $V_{CC}$ to $V_{EE}$ )	$V_S$	+36	V
Input Differential Voltage Range (Note 1)	$V_{IDR}$	$\pm 30$	V
Input Voltage Range (Notes 1 and 2)	$V_{IR}$	$\pm 15$	V
Output Short Circuit Duration (Note 3)	$t_{SC}$	Indefinite	sec
Operating Junction Temperature	$T_J$	+150	$^{\circ}\text{C}$
Storage Temperature Range	$T_{stg}$	-60 to +150	$^{\circ}\text{C}$

NOTES: 1. Differential voltages are at the noninverting input terminal with respect to the inverting input terminal.  
 2. The magnitude of the input voltage must never exceed the magnitude of the supply or 15 V, whichever is less.  
 3. Power dissipation must be considered to ensure maximum junction temperature ( $T_J$ ) is not exceeded. (See Figure 1.)

ELECTRICAL CHARACTERISTICS ( $V_{CC} = +15\text{ V}$ ,  $V_{EE} = -15\text{ V}$ ,  $T_A = 0^{\circ}$  to  $+70^{\circ}\text{C}$ , unless otherwise noted.)

Characteristics	Symbol	TL062AC TL064AC			TL062C TL064C			Unit
		Min	Typ	Max	Min	Typ	Max	
Input Offset Voltage ( $R_S = 50\ \Omega$ , $V_O = 0\text{ V}$ ) $T_A = 25^{\circ}\text{C}$ $T_A = 0^{\circ}$ to $+70^{\circ}\text{C}$	$V_{IO}$	—	3.0	6.0 7.5	—	3.0 15	20	mV
Average Temperature Coefficient for Offset Voltage ( $R_S = 50\ \Omega$ , $V_O = 0\text{ V}$ )	$\Delta V_{IO}/\Delta T$	—	10	—	—	10	—	$\mu\text{V}/^{\circ}\text{C}$
Input Offset Current ( $V_{CM} = 0\text{ V}$ , $V_O = 0\text{ V}$ ) $T_A = 25^{\circ}\text{C}$ $T_A = 0^{\circ}$ to $+70^{\circ}\text{C}$	$I_{IO}$	—	0.5	100 2.0	—	0.5 2.0	200	pA nA
Input Bias Current ( $V_{CM} = 0\text{ V}$ , $V_O = 0\text{ V}$ ) $T_A = 25^{\circ}\text{C}$ $T_A = 0^{\circ}$ to $+70^{\circ}\text{C}$	$I_{IB}$	—	3.0	200 2.0	—	3.0 2.0	200	pA nA
Input Common Mode Voltage Range $T_A = 25^{\circ}\text{C}$	$V_{ICR}$	—	+14.5 -11.5	+11.5 -12.0	—	+14.5 -12.0	+11	V
Large Signal Voltage Gain ( $R_L = 10\text{ k}\Omega$ , $V_O = \pm 10\text{ V}$ ) $T_A = 25^{\circ}\text{C}$ $T_A = 0^{\circ}$ to $+70^{\circ}\text{C}$	$A_{VOL}$	4.0 4.0	58 —	—	3.0 3.0	58 —	—	V/mV
Output Voltage Swing ( $R_L = 10\text{ k}\Omega$ , $V_{IO} = 1.0\text{ V}$ ) $T_A = 25^{\circ}\text{C}$ $T_A = 0^{\circ}$ to $+70^{\circ}\text{C}$	$V_{O+}$ $V_{O-}$	+10 —	+14 -14	— -10	+10 —	+14 -14	— -10	V
Common Mode Rejection ( $R_S = 50\ \Omega$ , $V_{CM} = V_{ICR\ min}$ , $V_O = 0\text{ V}$ , $T_A = 25^{\circ}\text{C}$ )	CMR	80	84	—	70	84	—	dB
Power Supply Rejection ( $R_S = 50\ \Omega$ , $V_{CM} = 0\text{ V}$ , $V_O = 0$ , $T_A = 25^{\circ}\text{C}$ )	PSR	80	86	—	70	86	—	dB
Power Supply Current (each amplifier) (No Load, $V_O = 0\text{ V}$ , $T_A = 25^{\circ}\text{C}$ )	$I_D$	—	200	250	—	200	250	$\mu\text{A}$
Total Power Dissipation (each amplifier) (No Load, $V_O = 0\text{ V}$ , $T_A = 25^{\circ}\text{C}$ )	$P_D$	—	6.0	7.5	—	6.0	7.5	mW

TL062 TL064

TL062 TL064


DC ELECTRICAL CHARACTERISTICS (V<sub>CC</sub> = +15 V, V<sub>EE</sub> = -15 V, T<sub>A</sub> = T<sub>low</sub> to T<sub>high</sub> [Note 4], unless otherwise noted.)

Characteristics	Symbol	TL062V			TL064V			Unit
		Min	Typ	Max	Min	Typ	Max	
Input Offset Voltage (R <sub>S</sub> = 50 Ω, V <sub>O</sub> = 0 V) T <sub>A</sub> = 25°C T <sub>A</sub> = T <sub>low</sub> to T <sub>high</sub>	V <sub>IO</sub>	—	3.0	6.0	—	3.0	9.0	mV
Average Temperature Coefficient for Offset Voltage (R <sub>S</sub> = 50 Ω, V <sub>O</sub> = 0 V)	ΔV <sub>IO</sub> /ΔT	—	10	—	—	10	—	μV/°C
Input Offset Current (V <sub>CM</sub> = 0 V, V <sub>O</sub> = 0 V) T <sub>A</sub> = 25°C T <sub>A</sub> = T <sub>low</sub> to T <sub>high</sub>	I <sub>IO</sub>	—	5.0	100	—	5.0	100	pA nA
Input Bias Current (V <sub>CM</sub> = 0 V, V <sub>O</sub> = 0 V) T <sub>A</sub> = 25°C T <sub>A</sub> = T <sub>low</sub> to T <sub>high</sub>	I <sub>IB</sub>	—	30	200	—	30	200	pA nA
Input Common Mode Voltage Range (T <sub>A</sub> = 25°C)	V <sub>ICR</sub>	—	+14.5	+11.5	—	+14.5	+11.5	V
Large Signal Voltage Gain (R <sub>L</sub> = 10 kΩ, V <sub>O</sub> = ±10 V) T <sub>A</sub> = 25°C T <sub>A</sub> = T <sub>low</sub> to T <sub>high</sub>	A <sub>vOL</sub>	4.0	58	—	4.0	58	—	V/mV
Output Voltage Swing (R <sub>L</sub> = 10 kΩ, V <sub>ID</sub> = 1.0 V) T <sub>A</sub> = 25°C T <sub>A</sub> = T <sub>low</sub> to T <sub>high</sub>	V <sub>O+</sub> V <sub>O-</sub> V <sub>O+</sub> V <sub>O-</sub>	+10 — +10 —	+14 -14 — -10	-10 — +10 —	+10 — +10 —	-14 — -10 —	— — — -10	V
Common Mode Rejection (R <sub>S</sub> = 50 Ω, V <sub>CM</sub> = V <sub>ICR</sub> min, V <sub>O</sub> = 0, T <sub>A</sub> = 25°C)	CMR	80	84	—	80	84	—	dB
Power Supply Rejection (R <sub>S</sub> = 50 Ω, V <sub>CM</sub> = 0 V, V <sub>O</sub> = 0, T <sub>A</sub> = 25°C)	PSR	80	86	—	80	86	—	dB
Power Supply Current (each amplifier) (No Load, V <sub>O</sub> = 0 V, T <sub>A</sub> = 25°C)	I <sub>D</sub>	—	200	250	—	200	250	μA
Total Power Dissipation (each amplifier) (No Load, V <sub>O</sub> = 0 V, T <sub>A</sub> = 25°C)	P <sub>D</sub>	—	6.0	7.5	—	6.0	7.5	mW

NOTE: 4. T<sub>low</sub> = -40°C T<sub>high</sub> = +85°C for TL062,4V

AC ELECTRICAL CHARACTERISTICS (V<sub>CC</sub> = +15 V, V<sub>EE</sub> = -15 V, T<sub>A</sub> = +25°C, unless otherwise noted.)

Characteristics	Symbol	Min	Typ	Max	Unit
Slew Rate (V <sub>IN</sub> = -10 V to +10 V, R <sub>L</sub> = 10 kΩ, C <sub>L</sub> = 100 pF, A <sub>v</sub> = +1.0)	SR	2.0	6.0	—	V/μs
Rise Time (V <sub>IN</sub> = 20 mV, R <sub>L</sub> = 10 kΩ, C <sub>L</sub> = 100 pF, A <sub>v</sub> = +1.0)	t <sub>r</sub>	—	0.1	—	μs
Overshoot (V <sub>IN</sub> = 20 mV, R <sub>L</sub> = 10 kΩ, C <sub>L</sub> = 100 pF, A <sub>v</sub> = +1.0)	OS	—	10	—	%
Settling Time (V <sub>CC</sub> = +15 V, V <sub>EE</sub> = -15 V, A <sub>v</sub> = -1.0, R <sub>L</sub> = 10 kΩ, V <sub>O</sub> = 0 V to +10 V step) To within 10 mV To within 1.0 mV	t <sub>S</sub>	—	1.6	—	μs
Gain Bandwidth Product (f = 200 kHz)	GBW	—	2.0	—	MHz
Equivalent Input Noise (R <sub>S</sub> = 100 Ω, f = 1.0 kHz)	e <sub>n</sub>	—	47	—	nV/√Hz
Input Resistance	R <sub>i</sub>	—	1012	—	W
Channel Separation (f = 10 kHz)	CS	—	120	—	dB

Motorola reserves the right to make changes without further notice to any products herein. Motorola makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Motorola assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters which may be provided in Motorola data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. Motorola does not convey any license under its patent rights nor the rights of others. Motorola products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the Motorola product could create a situation where personal injury or death may occur. Should Buyer purchase or use Motorola products for any such unintended or unauthorized application, Buyer shall indemnify and hold Motorola and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Motorola was negligent regarding the design or manufacture of the part. Motorola and  are registered trademarks of Motorola, Inc. Motorola, Inc. is an Equal Opportunity/Affirmative Action Employer.







How to reach us:  
**USA/EUROPE/Locations Not Listed:** Motorola Literature Distribution,  
 P.O. Box 20912, Phoenix, Arizona 85038. 1-800-441-2447 or 602-303-6654  
**MFAX:** RMFAX00@email.sps.mot.com — TOUCHSTONE 602-244-6609  
**INTERNET:** http://Design-NET.com

**JAPAN:** Nippon Motorola Ltd., Tabsum-SPO-JLDC, 6F Seibu-Butsuryu-Center,  
 3-14-2 Tatsumi Koto-Ku, Tokyo 135, Japan. 03-81-3521-8315  
**ASIA/PACIFIC:** Motorola Semiconductors H.K. Ltd., 8B Tai Ping Industrial Park,  
 51 Ting Kok Road, Tai Po, N.T., Hong Kong. 852-26529298



TL062 TL064  
NOTES







TL062 TL064



Electrónica S.A. de C.V.

TL062 TL064


TL062 TL064  
NOTES



TL062 TL064

OUTLINE DIMENSIONS


N SUFFIX  
PLASTIC PACKAGE  
CASE 646-06  
ISSUE L



- NOTES:
- LEADS WITHIN 0.13 (0.005) RADIUS OF TRUE POSITION AT SEATING PLANE AT MAXIMUM MATERIAL CONDITION.
  - DIMENSION TO CENTER OF LEADS WHEN FORMED PARALLEL.
  - DIMENSION DOES NOT INCLUDE MOLD FLASH.
  - ROUNDED CORNERS OPTIONAL.

DIM	MIN	MAX	MIN	MAX
A	0.715	0.735	0.15	0.165
B	0.245	0.255	0.10	0.10
C	0.125	0.135	0.05	0.05
D	0.015	0.021	0.38	0.43
E	0.045	0.055	1.00	1.10
F	0.100	0.105	2.54	2.54
G	0.050	0.055	1.27	1.27
H	0.050	0.055	1.27	1.27
J	0.050	0.055	0.20	0.20
K	0.115	0.115	3.42	3.43
L	0.000	0.000	7.62	7.62
M	0.1	0.1	0.7	0.7
N	0.01	0.01	0.25	0.25
P	0.01	0.01	0.25	0.25
Q	0.01	0.01	0.25	0.25
R	0.01	0.01	0.25	0.25
S	0.01	0.01	0.25	0.25
T	0.01	0.01	0.25	0.25
U	0.01	0.01	0.25	0.25
V	0.01	0.01	0.25	0.25
W	0.01	0.01	0.25	0.25
X	0.01	0.01	0.25	0.25
Y	0.01	0.01	0.25	0.25
Z	0.01	0.01	0.25	0.25

D SUFFIX  
PLASTIC PACKAGE  
CASE 751A-03  
(SO-14)  
ISSUE F



- NOTES:
- DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
  - CONTROLLING DIMENSION MILLIMETER. DIMENSIONS AND B DO NOT INCLUDE MOLD PROTRUSION.
  - MAXIMUM MOLD PROTRUSION 0.15 (0.006) PER SIDE.
  - DIMENSION DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.127 (0.005) TOTAL IN EXCESS OF THE D DIMENSION AT MAXIMUM MATERIAL CONDITION.

DIM	MIN	MAX	MIN	MAX
A	8.55	8.75	0.335	0.345
B	3.80	4.00	0.150	0.157
C	1.25	1.25	0.050	0.050
D	0.35	0.48	0.014	0.020
E	0.60	0.70	0.024	0.028
F	0.10	0.10	0.002	0.002
G	1.27	1.27	0.050	0.050
H	0.10	0.10	0.002	0.002
J	0.10	0.10	0.002	0.002
K	0.10	0.10	0.002	0.002
L	0.10	0.10	0.002	0.002
M	0.10	0.10	0.002	0.002
N	0.10	0.10	0.002	0.002
P	0.10	0.10	0.002	0.002
Q	0.10	0.10	0.002	0.002
R	0.10	0.10	0.002	0.002
S	0.10	0.10	0.002	0.002
T	0.10	0.10	0.002	0.002
U	0.10	0.10	0.002	0.002
V	0.10	0.10	0.002	0.002
W	0.10	0.10	0.002	0.002
X	0.10	0.10	0.002	0.002
Y	0.10	0.10	0.002	0.002
Z	0.10	0.10	0.002	0.002

TL062 TL064

Figure 13. Power Supply Rejection versus Frequency




Figure 14. Normalized Gain Bandwidth Product, Slew Rate and Phase Margin versus Temperature




Figure 15. Input Bias Current versus Temperature




Figure 16. Input Noise Voltage versus Frequency




Figure 17. Small Signal Response





Figure 18. Large Signal Response



TL062 TL064

Figure 19. AC Amplifier




Figure 20. High-Q Notch Filter




Figure 21. Instrumentation Amplifier




Figure 22. 0.5 Hz Square-Wave Oscillator





Figure 23. Audio Distribution Amplifier



TL062 TL064

OUTLINE DIMENSIONS

P SUFFIX  
PLASTIC PACKAGE  
CASE 626-05  
ISSUE K

NOTES:  
1. DIMENSION L TO CENTER OF LEAD WHEN FORMED PARALLEL.  
2. PACKAGE CONTOUR OPTIONAL (ROUND OR SQUARE CORNERS).  
3. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.

MILLIMETERS		INCHES	
DIM.	MIN.	MAX.	MIN.
A	2.42	10.16	0.370
B	1.27	6.80	0.500
C	3.34	4.45	0.130
D	0.28	0.71	0.011
E	0.18	0.71	0.007
F	2.54	3.05	0.100
G	0.76	1.27	0.030
H	0.25	0.30	0.010
J	0.25	0.30	0.010
K	0.25	0.30	0.010
L	7.62	8.89	0.300
M	0.10	0.10	0.004
N	0.25	1.01	0.010

D SUFFIX  
PLASTIC PACKAGE  
CASE 751-05  
(SO-8)  
ISSUE R

NOTES:  
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1984.  
2. DIMENSIONS ARE IN MILLIMETERS.  
3. DIMENSION D AND E DO NOT INCLUDE MOLD PROTRUSION.  
4. MAXIMUM MOLD PROTRUSION 0.15 PER SIDE.  
5. DIMENSION B DOES NOT INCLUDE MOLD PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.27 TOTAL IN EXCESS OF THE B DIMENSION AT MAXIMUM MATERIAL CONDITION.

MILLIMETERS	
DIM.	MIN. MAX.
A	1.25 1.75
B	0.30 0.49
C	0.15 0.25
D	4.80 5.00
E	1.90 2.00
F	1.27 1.50
G	0.25 0.50
H	0.40 1.25