




µA741µA741Y
GENERAL-PURPOSE OPERATIONAL AMPLIFIER

SLOS094A ± NOVEMBER 1970 ± REVISED JANUARY 1992

TYPICAL CHARACTERISTICS



µA741µA741Y
GENERAL-PURPOSE OPERATIONAL AMPLIFIERS


SLOS094A ± NOVEMBER 1970 ± REVISED JANUARY 1992

AVAILABLE OPTIONS

T _A	PACKAGED DEVICES							CHIP FORM (Y)
	SMALL OUTLINE (D)	CHIP CARRIER (FK)	CERAMIC DIP (J)	CERAMIC DIP (JG)	PLASTIC DIP (P)	TSSOP (PW)	FLAT PACK (U)	
0°C to 70°C	µA741CD				µA741CP	µA741CPW		µA741Y
±40°C to 85°C	µA741D				µA741IP			
±55°C to 125°C		µA741MFK	µA741MJ	µA741MJG			µA741MU	

The D package is available taped and reeled. Add the suffix R (e.g., µA741CDR).

schematic




nA741nA741Y
 GENERAL-PURPOSE OPERATIONAL AMPLIFIER

SLOS094A ± NOVEMBER 1970 ± REVISED JANUARY 1992

nA741Y chip information

This chip, when properly assembled, displays characteristics similar to the nA741C. Thermal compression or ultrasonic bonding may be used on the doped-aluminum bonding pads. Chips may be mounted with conductive epoxy or a gold-silicon preform.



nA741nA741Y
 GENERAL-PURPOSE OPERATIONAL AMPLIFIERS

SLOS094A ± NOVEMBER 1970 ± REVISED JANUARY 1992

TYPICAL CHARACTERISTICS²




Figure 3

Figure 4




Figure 5

² Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

mA741mA741Y
GENERAL-PURPOSE OPERATIONAL AMPLIFIER

SLOS094A ± NOVEMBER 1970 ± REVISED JANUARY 1992

PARAMETER MEASUREMENT INFORMATION




Figure 1. Rise Time, Overshoot, and Slew Rate

APPLICATION INFORMATION

Figure 2 shows a diagram for an input offset voltage null circuit.




Figure 2. Input Offset Voltage Null Circuit



**TEXAS
INSTRUMENTS**
POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

mA741mA741Y
GENERAL-PURPOSE OPERATIONAL AMPLIFIERS

SLOS094A ± NOVEMBER 1970 ± REVISED JANUARY 1992

absolute maximum ratings over operating free-air temperature range (unless otherwise noted)

	■7411C	■7411	■7411M	UNIT
Supply voltage, V_{CC+} (see Note 1)	18	22	22	V
Supply voltage, V_{CC-} (see Note 1)	±18	±22	±22	V
Differential input voltage, V_{IP} (see Note 2)	±15	±30	±30	V
Input voltage, V_I any input (see Notes 1 and 3)	±15	±15	±15	V
Voltage between offset null (either OFFSET N1 or OFFSET N2) and V_{CC+}	±15	+0.5	+0.5	V
Duration of output short circuit (see Note 4)	unlimited	unlimited	unlimited	
Continuous total power dissipation	See Dissipation Rating Table			
Operating free-air temperature range, T_A	0 to 70	±40 to 85	±55 to 125	°C
Storage temperature range	±65 to 150	±65 to 150	±65 to 150	°C
Case temperature for 60 seconds	FK package		260	°C
Lead temperature 1.6 mm (1/16 inch) from case for 60 seconds	J, JG, or U package		300	°C
Lead temperature 1.6 mm (1/16 inch) from case for 10 seconds	D, P, or PW package	260	260	°C

² Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

- NOTES:
1. All voltage values, unless otherwise noted, are with respect to the midpoint between V_{CC+} and V_{CC-} .
 2. Differential voltages are at IN+ with respect to IN-.
 3. The magnitude of the input voltage must never exceed the magnitude of the supply voltage or 15 V, whichever is less.
 4. The output may be shorted to ground or other power supply. For the m741M only, the unlimited duration of the short circuit applies at (or below) 125°C case temperature or 75°C free-air temperature.

DISSIPATION RATING TABLE

PACKAGE	T _A ≤ 25°C POWER RATING	DERATING FACTOR	DERATE ABOVE T _A	T _A = 70°C POWER RATING	T _A = 85°C POWER RATING	T _A = 125°C POWER RATING
D	500 mW	5.8 mW/°C	64°C	464 mW	377 mW	N/A
FK	500 mW	11.0 mW/°C	105°C	500 mW	500 mW	275 mW
J	500 mW	11.0 mW/°C	105°C	500 mW	500 mW	275 mW
P	500 mW	8.0 mW/°C	99°C	500 mW	500 mW	210 mW
3	500 mW	N/A	N/A	500 mW	500 mW	N/A
PW	525 mW	4.2 mW/°C	25°C	338 mW	N/A	N/A
U	500 mW	5.4 mW/°C	57°C	432 mW	351 mW	135 mW



TEXAS INSTRUMENTS
POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

µA741 µA741Y GENERAL-PURPOSE OPERATIONAL AMPLIFIER

SLOS094A ± NOVEMBER 1970 ± REVISED JANUARY 1992

electrical characteristics at specified free-air temperature, V $CC_{\pm} = \pm 15$ V (unless otherwise noted)

PARAMETER	TEST CONDITIONS	T_A^1	µA741C			µA741L, µA741M			UNIT
			MIN	TYP	MAX	MIN	TYP	MAX	
V_{IO}	Input offset voltage	$V_O = 0$	25°C			1			mV
			Full range			7.5			
$DV_{IO(adj)}$	Offset voltage adjust range	$V_O = 0$	25°C			±15			mV
I_O	Input offset current	$V_O = 0$	25°C			20			nA
			Full range			300			
I_{IB}	Input bias current	$V_O = 0$	25°C			80			nA
			Full range			500			
V_{ICR}	Common-mode input voltage range		25°C			±12			V
			Full range			±12			
V_{OM}	Maximum peak output voltage swing	$R_L = 10$ kW	25°C			±12			V
		$R_L = 2$ kW	Full range			±12			
		$R_L = 2$ kW	25°C			±10			
		$R_L = 2$ kW	Full range			±10			
A_{VD}	Large-signal differential voltage amplification	$R_L = 2$ kW	25°C			20			V/mV
		$V_O = \pm 10$ V	Full range			15			
r_i	Input resistance	25°C	0.3			2			MW
r_o	Output resistance	$V_O = 0$, See Note 5	25°C			75			W
C_i	Input capacitance	25°C	1.4			1.4			pF
CMRR	Common-mode rejection ratio	$V_{IC} = V_{ICRmin}$	25°C			70			dB
			Full range			70			
k_{SVS}	Supply voltage sensitivity (DV_{IO}/DV_{CC})	25°C	30			150			mV/V
		$V_{CC} = \pm 9$ V to ± 15 V	Full range			150			
I_{OS}	Short-circuit output current	25°C	±25			±40			mA
I_{CC}	Supply current	$V_O = 0$, No load	25°C			1.7			mA
			Full range			3.3			
P_D	Total power dissipation	25°C	50			85			mW
		$V_O = 0$, No load	Full range			100			

¹ All characteristics are measured under open-loop conditions with zero common-mode input voltage unless otherwise specified. Full range for the µA741C is 0°C to 70°C, the µA741L is ±40°C to 85°C, and the µA741M is ±55°C to 125°C.

NOTE 5: This typical value applies only at frequencies above a few hundred hertz because of the effects of drift and thermal feedback.

operating characteristics, V $CC_{\pm} = \pm 15$ V, $T_A = 25^\circ\text{C}$

PARAMETER	TEST CONDITIONS	µA741C			µA741L, µA741M			UNIT
		MIN	TYP	MAX	MIN	TYP	MAX	
t_r	Rise time	$V_i = 20$ mV, $R_L = 2$ kW,			0.3			ms
	Overhoot factor	$C_L = 100$ pF, See Figure 1			5%			
SR	Slew rate at unity gain	$V_i = 10$ V, $R_L = 2$ kW,			0.5			V/ms
		$C_L = 100$ pF, See Figure 1						

µA741 µA741Y GENERAL-PURPOSE OPERATIONAL AMPLIFIERS

SLOS094A ± NOVEMBER 1970 ± REVISED JANUARY 1992

electrical characteristics at specified free-air temperature, V $CC_{\pm} = \pm 15$ V, $T_A = 25^\circ\text{C}$ (unless otherwise noted)

PARAMETER	TEST CONDITIONS	µA741Y			UNIT
		MIN	TYP	MAX	
V_{IO}	Input offset voltage	$V_O = 0$	1	6	mV
$DV_{IO(adj)}$	Offset voltage adjust range	$V_O = 0$	±15		mV
I_O	Input offset current	$V_O = 0$	20	200	nA
I_{IB}	Input bias current	$V_O = 0$	80	500	nA
V_{ICR}	Common-mode input voltage range		±12	±13	V
V_{OM}	Maximum peak output voltage swing	$R_L = 10$ kW	±12	±14	V
		$R_L = 2$ kW	±10	±13	
A_{VD}	Large-signal differential voltage amplification	$R_L = 2$ kW	20	200	V/mV
r_i	Input resistance		0.3	2	MW
r_o	Output resistance	$V_O = 0$, See Note 5		75	W
C_i	Input capacitance			1.4	pF
CMRR	Common-mode rejection ratio	$V_{IC} = V_{ICRmin}$	70	90	dB
k_{SVS}	Supply voltage sensitivity (DV_{IO}/DV_{CC})	$V_{CC} = \pm 9$ V to ± 15 V	30	150	mV/V
I_{OS}	Short-circuit output current		±25	±40	mA
I_{CC}	Supply current	$V_O = 0$, No load	1.7	2.8	mA
P_D	Total power dissipation	$V_O = 0$, No load	50	85	mW

¹ All characteristics are measured under open-loop conditions with zero common-mode voltage unless otherwise specified.

NOTE 5: This typical value applies only at frequencies above a few hundred hertz because of the effects of drift and thermal feedback.

operating characteristics, V $CC_{\pm} = \pm 15$ V, $T_A = 25^\circ\text{C}$

PARAMETER	TEST CONDITIONS	µA741Y			UNIT
		MIN	TYP	MAX	
t_r	Rise time	$V_i = 20$ mV, $R_L = 2$ kW,	0.3		ms
	Overhoot factor	$C_L = 100$ pF, See Figure 1	5%		
SR	Slew rate at unity gain	$V_i = 10$ V, $R_L = 2$ kW,	0.5		V/ms
		$C_L = 100$ pF, See Figure 1			