


UCL

Chip Type, Low Impedance





- Chip type, low impedance, temperature range up to +105°C.
- Applicable to automatic mounting machine fed with carrier tape.
- Compliant to the RoHS directive (2011/65/EU, (EU)2015/863).
- AEC-Q200 compliant. Please contact us for details.



Specifications

Item	Performance Characteristics						
Category Temperature Range	- 55 to +105°C						
Rated Voltage Range	6.3 to 50V						
Rated Capacitance Range	10 to 2200μF						
Capacitance Tolerance	± 20% at 120Hz, 20°C						
Leakage Current	After 2 minutes' application of rated voltages at 20°C, leakage current is not more than 0.01 CV or 3 (μA), whichever is greater.						
Tangent of loss angle (tan δ)	Measurement frequency : 120Hz at 20°C						
	Rated voltage (V)	6.3	10	16	25	35	50
	tan δ (MAX.)	0.26	0.19	0.16	0.14	0.12	0.10
Stability at Low Temperature	Measurement frequency : 120Hz						
	Rated voltage (V)	6.3	10	16	25	35	50
	Impedance ratio	Z-25°C / Z+20°C	2	2	2	2	2
	ZT / Z20 (MAX.)	Z-40°C / Z+20°C	3	3	3	3	3
		Z-55°C / Z+20°C	4	4	4	3	3
Endurance	The specifications listed at right shall be met when the capacitors are restored to 20°C after the rated voltage is applied for 2000 hours at 105°C.			Capacitance Change		Within ± 30% of the initial capacitance value	
				tan δ		200% or less than the initial specified value	
				Leakage current		Less than or equal to the initial specified value	
Shelf Life	After storing the capacitors under no load at 105°C for 1000 hours and then performing voltage treatment based on JIS C 5101-4 clause 4.1 at 20°C, they shall meet the specified values for the endurance characteristics listed above.						
Resistance to soldering heat	The capacitors are kept on a hot plate for 30 seconds, which is maintained at 250°C. The capacitors shall meet the characteristic requirements listed at right when they are removed from the plate and restored to 20°C .			Capacitance Change		Within ± 10% of the initial capacitance value	
				tan δ		Less than or equal to the initial specified value	
				Leakage current		Less than or equal to the initial specified value	
Marking	Black print on the case top.						

Chip Type




Voltage

V	6.3	10	16	25	35	50
Code	j	A	C	E	V	H

• Dimension table in next page.

Type numbering system (Example : 16V 100μF)



	(mm)								
φD × L	4 × 5.8	5 × 5.8	6.3 × 5.8	6.3 × 7.7	8 × 6.2	8 × 10	10 × 7.7	10 × 10	10 × 13.5
A	1.8	2.1	2.4	2.4	3.3	2.9	3.2	3.2	3.2
B	4.3	5.3	6.6	6.6	8.3	8.3	10.3	10.3	10.3
C	4.3	5.3	6.6	6.6	8.3	8.3	10.3	10.3	10.3
E	1.0	1.3	2.2	2.2	2.3	3.1	4.5	4.5	4.5
L	5.8	5.8	5.8	7.7	6.2	10	7.7	10	13.5
H	0.5 to 0.8	0.5 to 0.8	0.5 to 0.8	0.5 to 0.8	0.5 to 0.8	0.8 to 1.1	0.8 to 1.1	0.8 to 1.1	0.8 to 1.1

UCL

■ Dimensions

Cap. (μF)	V	6.3			10			16			25			35			50		
		0J			1A			1C			1E			1V			1H		
10	100							4 × 5.8	0.85	160	4 × 5.8	0.85	160	● 4 × 5.8 5 × 5.8	0.85 0.36	160 240			
22	220	4 × 5.8	0.85	160	4 × 5.8	0.85	160	● 4 × 5.8 5 × 5.8	0.85 0.36	160 240	5 × 5.8	0.36	240	5 × 5.8	0.36	240			
33	330				● 4 × 5.8 5 × 5.8	0.85 0.36	160 240				● 5 × 5.8 6.3 × 5.8	0.36 0.26	240 300	6.3 × 5.8	0.26	300			
47	470	● 4 × 5.8 5 × 5.8	0.85 0.36	160 240	6.3 × 5.8	0.26	300	● 5 × 5.8 6.3 × 5.8	0.36 0.26	240 300	6.3 × 5.8	0.26	300	6.3 × 5.8	0.26	300			
68	680							6.3 × 5.8	0.26	300	6.3 × 5.8	0.26	300	6.3 × 7.7	0.16	600			
100	101	● 5 × 5.8 6.3 × 5.8	0.36 0.26	240 300	6.3 × 5.8	0.26	300	6.3 × 5.8 ● 6.3 × 7.7	0.26 0.16	300 600	6.3 × 7.7 ● 8 × 6.2	0.16 0.18	600 500	● 6.3 × 7.7 8 × 10	0.16 0.08	600 850	8 × 10	0.18	670
150	151				6.3 × 5.8	0.26	300	6.3 × 7.7	0.16	600	8 × 10 ● 10 × 7.7	0.08 0.10	850 850	8 × 10 ● 10 × 7.7	0.08 0.10	850 850			
220	221	6.3 × 5.8	0.26	300	6.3 × 7.7 ● 8 × 6.2	0.16 0.18	600 500	6.3 × 7.7 ● 8 × 6.2	0.16 0.18	600 500	8 × 10 ● 10 × 7.7	0.08 0.10	850 850	8 × 10 ● 10 × 7.7	0.08 0.10	850 850	10 × 10	0.12	900
330	331	6.3 × 7.7 ● 8 × 6.2	0.16 0.18	600 500	8 × 10 ● 10 × 7.7	0.08 0.10	850 850	8 × 10 ● 10 × 7.7	0.08 0.10	850 850	8 × 10	0.08	850	10 × 10	0.06	1190			
390	391													10 × 10	0.08	850			
470	471	8 × 10 ● 10 × 7.7	0.08 0.10	850 850	8 × 10 ● 10 × 7.7	0.08 0.10	850 850	8 × 10 ● 10 × 7.7	0.08 0.10	850 850	10 × 10	0.06	1190	10 × 13.5	0.06	1190			
560	561										10 × 10	0.08	850						
680	681				8 × 10	0.08	850	10 × 10	0.06	1190	10 × 13.5	0.06	1190						
820	821							10 × 10	0.08	850									
1000	102	8 × 10	0.08	850	10 × 10	0.06	1190	10 × 13.5	0.06	1190									
1200	122				10 × 10	0.08	850												
1500	152	10 × 10	0.06	1190	10 × 13.5	0.06	1190												
1800	182	10 × 10	0.08	850															
2200	222	10 × 13.5	0.06	1190													Case size φD × L (mm)	Impedance	Rated ripple

Max. Impedance (Ω) at 20°C 100kHz, Rated ripple current (mA rms) at 105°C 100kHz

●: In this case, [6] will be put at 12th digit of type numbering system.

● Frequency coefficient of rated ripple current

Frequency	50Hz	120Hz	300Hz	1kHz	10kHz or more
Coefficient	0.35	0.50	0.64	0.83	1.00

- Taping specifications are given in page 23.
- Recommended land size, soldering by reflow are given in page 18, 19.
- Please refer to page 3 for the minimum order quantity.