

UT120 series multimeters are designed for DIYers and electronics engineers to troubleshoot electronics systems development and electronics circuits. It is a simple and portable multimeter for every electronics engineer.



UT120C



Specifications	Range	UT120A	UT120B	UT120C
Certificates	CE, UKCA, cETLus (UT120A/UT120B)			
DC voltage (V)	600V	$\pm(0.8\%+1)$	$\pm(0.8\%+1)$	$\pm(0.8\%+1)$
AC voltage (V)	600V	$\pm(1.2\%+3)$	$\pm(1.2\%+3)$	$\pm(1.2\%+3)$
DC current (A)	400mA			$\pm(1\%+3)$
AC current (A)	400mA			$\pm(1.5\%+5)$
Resistance (Ω)	40M Ω	$\pm(1\%+2)$	$\pm(1\%+2)$	$\pm(1\%+2)$
Capacitance (F)	100 μ F		$\pm(4\%+3)$	$\pm(4\%+3)$
Frequency (Hz)	100kHz	$\pm(0.5\%+3)$	$\pm(0.5\%+3)$	$\pm(0.5\%+3)$
Display count	4000			
Category ratings	CAT II 600V			

Features	
Auto range	Duty cycle: 0.1%~99.9%
Diode	Auto power off
Continuity buzzer	Low battery indication: $\leq 2.4V$
Data hold	Relative mode

Characteristics	
Standard accessories	Blister, English manual
Power	3V battery (CR2032)
Display	43 x 22mm
Product size	110 x 58.2 x 10.8mm
Product net weight	76g
Standard individual packing	Gift box
Standard quantity per carton	60pcs
Standard carton measurement	430 x 255 x 460mm
Standard carton gross weight	11.5kg