



UT333S

UT333S is a stable, safe and reliable mini digital temperature humidity meter. With split type design, it is convenient to measure the temperature accurately in different environments. It is widely used in grain storage and transportation, material management, forestry and animal husbandry, healthcare, education, and home. The split type design is perfect for monitoring hard to reach places and small ventilation ducts.



| Specifications | Range | Resolution | Accuracy |
|----------------|-----------------------|-------------|-----------|
| Certificates | CE, UKCA | | |
| Temperature | -10°C~60°C/14°F~140°F | 0.1°C/0.2°F | ±1°C/±2°F |
| Humidity | 0%RH~100%RH | 0.1%RH | ±5% |

| Features | |
|-----------|----------------|
| °C/°F | Data hold |
| MAX/MIN | Overload alarm |
| Backlight | Auto power off |

| Characteristics | |
|------------------------------|---------------------------|
| Standard accessories | Batteries, English manual |
| Power | 1.5V battery (R03) x 3 |
| Display | 32 x 35mm |
| Product size | 110 x 53 x 26mm |
| Product net weight | 310g |
| Standard individual packing | Gift box, blister |
| Standard quantity per carton | 20pcs |
| Standard carton measurement | 480 x 300 x 360mm |
| Standard carton gross weight | 6.7kg |

Para mayor información puede consultar el manual de usuario dando clic en el siguiente enlace:
<https://meters.uni-trend.com/download/ut333s-user-manual/?wpdmdl=7281&refresh=661de021273f61713233953>