



UT681L

UT681C

UT681HDMI

Specifications	Description	UT681L	UT681C	UT681HDMI
Certificates	CE, UKCA			
To test for: RJ45/RJ11		√		
To test for: RJ45/RJ11/BNC	Need to use RJ45 to BNC adaptor		√	
To test for: HDMI/MINI-HDMI				√
Fast test mode	LED1~LED8, LED_G	√	√	
Slow test mode	LED1~LED8, LED_G	√	√	
Scan test mode	LED1~LED19, LED_S			√
Full display test mode	LED1~LED19, LED_S			√
To test for the case of short circuit, crossover, open circuit, etc.		√	√	√
Ethernet cable: shielded/ unshielded test		√	√	√
Manual shutdown function		√	√	√
Auto shutdown function	No operation within 10 minutes	√	√	√
Single key operation		√	√	√
Power supply: 9V battery		√	√	√
Low battery detection	Less than 7.2V	√	√	√
Working temperature: 0°C~40°C		√	√	√
Storage temperature: -10°C~50°C		√	√	√
Working humidity: 20~80%RH		√	√	√
Storage humidity: 10~90%RH		√	√	√
Altitude: ≤2000 meters		√	√	√
Safety standard	EN61326-1: 2013; EN61326-2-2: 2013	√	√	√

Characteristics	
Standard accessories	9V battery, BNC to RJ45 adaptor (UT681C), English manual
Product size	Transmitter: 102 x 62 x 28mm; receiver: 102 x 37 x 28mm
Product net weight	Transmitter: 87g; receiver: 51g
Standard individual packing	Gift box
Standard quantity per carton	40pcs
Standard carton measurement	455 x 410 x 225mm
Standard carton gross weight	UT681L: 6.4kg; UT681C: 8.7kg; UT681HDMI: 9.5kg

Para mayor información puede consultar el manual de usuario dando clic en el siguiente enlace:
<https://meters.uni-trend.com/download/ut681hdm-user-manual/?wpdmdl=7747&refresh=661f787656faa1713338486>