

UT213 series are 400A digital clamp meters with CAT III 600V safety standards. These meters are designed for electricians and HVAC/R technicians. The built-in flashlight also makes these meters useful tools when working in dark environments.



UT213C

Specifications	Range	UT213A	UT213B	UT213C
Certificates	CE, UKCA, cETLus			
AC current (A)	400A	±(1.8%+9)	±(1.8%+9)	±(2.5%+5)
DC current (A)	400A			±(2%+3)
AC voltage (V)	600V	±(1.2%+5)	±(1.2%+5)	±(1.2%+5)
DC voltage (V)	600V	±(0.8%+1)	±(0.8%+1)	±(0.8%+3)
Resistance (Ω)	40MΩ	±(1%+2)	±(1%+2)	±(1%+2)
Capacitance (F)	100μF 40mF	±(1%+2)		±(4%+5)
Frequency	10Hz~1MHz	±(0.1%+4)	±(0.1%+4)	±(0.1%+4)
Temperature	-40°C~1000°C -40°F~1832°F		±(1%+3) ±(1%+6)	±(1%+3) ±(1%+6)
Display count		4000	4000	4000
Jaw opening		30mm	30mm	30mm
True RMS			√	√
Diode		Around 1.5V	Around 3.0V	Around 3.0V
MAX/MIN			√	√
Category ratings	CAT III 600V			

Features

Auto range	Flashlight
Relative mode	Low battery indication: ≤3.6V
NCV/continuity buzzer	Input protection
Data hold/LCD backlight	Auto power off

Characteristics

Standard accessories	Batteries, test leads, point contact temperature probe (UT213B/UT213C), English manual
Power	1.5V battery (R03) x 3
Display	38 x 24mm
Product size	220 x 75 x 40mm
Product net weight	UT213A/B: 280g; UT213C: 231.7g
Standard individual packing	Gift box, carrying bag
Standard quantity per carton	20pcs
Standard carton measurement	485 x 345 x 205mm
Standard carton gross weight	UT213A: 9.1kg; UT213B: 9.8kg; UT213C: 9.7kg

Para mayor información puede consultar el manual de usuario dando clic en el siguiente enlace:

<https://meters.uni-trend.com/download/ut213a-b-c-user-manual/?wpdmdl=7215&refresh=62bf8b35811781656720181>