

UTi120T

Pocket-sized Thermal Camera

UTi120T is a pocket-sized and compact thermal camera, it can be easily put into pocket, which is very portable for users. Its 3.5" large LCD touch display screen is convenient for users to operate easily. It can automatically track the objective's temperature from $-20^{\circ}\text{C}\sim 400^{\circ}\text{C}$. It also supports Wi-Fi connection through UNI-T Mobile App. With this UTi120T thermal camera in the pocket, users will be ready anytime to diagnose electrical, mechanical, building problems and other potential issues.



■ UTi120T

- 3.5" large touch TFT screen
- IR Resolution: 120x90
- Wide temperature range: -20°C to 400°C
- Wi-Fi
- PC software
- With 640x480 digital camera and 1.0~8x continuous digital zoom
- IP54




» 3.5" large touch screen, easy to operate




» Pocket-sized, lightweight and portable

» Support Wi-Fi connection through UNI-T Mobile App and PC software





Applications

PCBA inspection, motor inspection, pipeline inspection, house water leakage inspection, power distribution cabinet inspection, automotive maintenance, electricity facilities inspection, mechanical equipment inspection, heating equipment inspection, building & HVAC inspection, etc.



Specifications

Model No.	UTi120T	
Product Photo		
Technical Data		
IR resolution (Pixels)	120×90	
Spatial resolution (IFOV)	7.6mrad	
Thermal sensitivity (NETD)	≤60mK	
Temperature measurement range	-20°C~400°C	
Frame rate	≤25Hz	
Display	3.5" TFT Touch (320x240)	
Field of view (FOV)	50°×38°	
Focus	Focus free	
Accuracy	±2°C or ±2% whichever is greater	
Emissivity	0.01~1.00 adjustable (0.95 default)	
Functions		
Color palettes	6 (White hot, Black hot, Ironbow, Hot iron, Arctic, Medical)	
Image modes	Thermal, Visual image, Fusion, PIP	
On screen analyzer	1 Point/1 Rectangle	
Digital camera resolution	640×480	
Digital zoom	1.0~8x continuous	
Hi/Lo temperature alarm	Icon, LED flashlight	
PC software analysis	√	
Wi-Fi	√	
General Characteristics		
Battery	Fixed Li-ion battery (3.7V 5000mAh)	
Battery operation time	≥2 hours (without Wi-Fi)	
USB	Type-C	
IP rating	IP54	
Drop proof	1m	
Storage	4GB Internal	
Image/Video storage format	JPEG	
Certificates	CE, FCC, RoHS	
Product net weight	212g	
Product size	205mm×124mm×65mm	
Packing Details		
Standard accessories	Hand strap, Carrying Bag, Micro SD card, Type-C USB cable, English manual, Documents download operation guide card	
Standard individual packing	Gift box	
Standard Qty per carton	5	
Standard carton size	370mm×250mm×170mm	
Standard carton G.W.	3.6kg	

Para mayor información puede consultar el manual de usuario dando clic en el siguiente enlace:
<https://thermal.uni-trend.com/download/uti120t/?wpdmdl=1921&refresh=63bc70bbf2d821673294011>

