


# BL SURGE ABSORBER

BL mini Surge Absorber (BLSA) , invented and produced by Japan BL Kogyo INC. , is a series of high-tech electronic components and is fully protected by international patent law . Its patent register number in Japan is HEI 7-16632 ; in USA: 08/378,969 ; in Korean: 2021/1995 ; in China: 94202711.6 . BL Surge Absorber is an innovated high-tech mini-size device .

## THE STRUCTURE OF BLSA



## THE FUNCTION OF BLSA SERIES

The surges such as those produced by high voltage transients, lightning, switching and noise spikes are the vital enemies of modern electronic equipment. Even the slightest interference of some common high voltage transients or noise spikes can cause errors in some semiconductor devices, or malfunction of computers, farther more result in the damage of the electronic equipment. Therefore, it is very necessary to eliminate and absorb the kinds of surge intrusion. Our BLSA is the best choice to carry on this protection function. It highly efficiently absorbs and eliminates those high voltage transients and protects electronic circuits from the damage caused by all kinds of surges and static. It improves the liability and prolongs the usage of electronic equipment, insures the quality of your products.

## THE MAJOR CHARACTERISTICS OF BLSA

BLSA is produced using silicon semiconductor as mediate inducing material and by our unique innovative processing technology based on the theory of high speed electronic reaction between a special type of super pure gas and silicon semiconductor. BLSA has its excellent clamping voltage characteristic and fast response time ( $>0.001\text{ps}$ ). It eliminates the discharge lag that is inductive of gap-type arrestors. It avoids the overheated damage happens in ZNR's type surge absorber (Zinc Oxide Nonlinear Resistor) due to their large electrostatic capacitance and leak current. BLSA also eliminates the variance in clamping voltage due to light effect that happens in some ionization gas tubes. BLSA's ideal bilateral and symmetrical V-I characteristic curve gives your circuits excellent clamping protection in either direction. Therefore, BLSA can be used both in AC and DC circuits to absorb surges by either positive or negative transients. BLSA can be used in circuits

in place of back-to-back zener diodes for bi-directional protection.


**BLSA Features:**

- Compared with other surge absorbers having similar functions , BLSA has the fast response speed , largest withstand current and voltage but smallest size
- Zero leaking current before clamping voltage
- All electrical characteristics are very stable even after long period of charge and discharge. There is no need for inspection and exchange periodically
- Super capability to withstand repeated lightning strikes
- Stable and very Small electrostatic capacitance (<0.8pf) and great isolation (>100MΩ)
- No pollution material
- Bilateral and symmetrical
- Completely insensitive to weather , temperature , humidity and lightness

BLSA thus provides a highly economical, reliable and unlimited duration way to protect against repeated quick rising edge surges and high voltage transients such as those produced by lighting, switching surges and noise spikes.


**BASIC ELECTRICAL DIAGRAMS AND COMPARISON**

Standard Impulse Current Waveform,8/20 us




**Maximum Peak Current Specification**  
 which specifies how much surge current, and surge absorber can endure is maximum peak current. That characteristics express a current value having standard wave form shown on the left .In case of different waveforms standard one, the specification shall determine referring to impulse life ratings.


10kv Fig-1.Lightning Original Waveform




10 kv Fig-2.YA-242M Absorption Waveform




10kv Fig-3.Electrostatic Original Waveform




10kv Fig-4.YP-201N Absorption Waveform



1kv Fig-5.Surge Original Waveform



1kv Fig-6.YS-301L Absorption Waveform



1kv Fig-7.Surge Original Waveform





Fig-8.ZNR (Zinc Oxide Nonlinear Resistor)  
1kv 270v Absorption Waveform



Flowing is the comparison of I-V characteristic for different products with  $V_s=300v$  using Curve Tracer:

Fig-9.ZNR Transient/surge Absorber





Fig-10.RSSA Surge Absorber




All series of BLSA can handle very large Maximum Peak Current and have very small electrostatic capacitance. These features give BLSA the outstanding capability to compress lightning strikes, surges and static spikes.

Fig-7 and Fig-8 show ZNR's characteristic when stricken by surge. Obvious, its capability to absorb surge and response time is affected by its bigger electrostatic capacitance and clamping point resistance.

Fig-11, I-V curve clearly shows that BLSA has very small resistance at the bilateral clamping point. Compared with other surge absorber, BLSA has ideal high-speed transient response.

Fig-11.BL Mini Surge Absorber



## THE APPLICATIONS OF BLSA

For Power Supplies (YA or YS series)

- Standard power supplies requisite by US UL1449
- Highly reliable power supplies
- Three or two phases industrial or civic machinery equipment power
- Power supplies for IC or electronic circuits
- Surge compressor for switch and relay

For Data Communication Equipment (YA, YS or YP Series)

- Standard protection required by US UL497A and UL497B
- Programmable switch machine
- Telephone
- Fax
- Modem

Equipment with Antenna or Antenna/Signal Circuits including mobile equipment (YS or YP series)

- Standard protection required by US UL1414
- Satellite Antenna
- Amplifier
- Cassette
- Radio
- Alarm and sensor

Equipment where Anti-static is Required (YS or YP series)


- Display including TV
- Monitor
- Environment where dusty and flammable material are presented

All kinds of Medical equipment and devices (YA , YS or YP series)

# YP Series:

Part Number	DC Spark-Over Voltage	Insulation Resistance	Electrostatic Capacitance 1KHZ-6Vmax	Surge current capacity	Surge Life
	V <sub>s</sub> (V)	IR(OHM)/DC	C(pf)	8/20us	Test
YP-141 N	140 ( 98~ 182)	>100M/100V	< 0.8	500A	1500pf-0OHM 10KV >200Times
YP-201 M	200 (160~ 240)				
YP-201 N	200 (140~ 260)				
YP-231 L	230 (196~ 265)				
YP-251 L	250 (212~ 287)				
YP-301 M	300 (240~ 360)				
YP-301 N	300 (210~ 390)				
YP-301 L	300 (255~ 345)				
YP-401 M	400 (320~ 480)				
YP-451 M	450 (360~ 540 )				
YP-501 M	500 (400~ 600)				
YP-601 M	600 (480~ 720)				
YP-701 M	700 (560~ 840)				
YP-102 M	1000 (800~ 1200)	>100M/500V			
YP-102 N	1000 (700 ~1300)				
YP-152 M	1500 (1200~1800)				
YP-152 N	1500 (1050~1950)				

## Dimension




## Color

Part Number	Color Code 1	Color Code 2	Color Code 3
141	Brown	Yellow	
201 M	Red		
201 N	Red	Red	
231 L	Red	Orange	
251	Red	Green	
301 L,M	Orange		
301 N	Orange	Orange	
401	Yellow		
451	Yellow	Green	
501	Green		
601	Blue		
701	Purple		
102 M	Black		
102 N	Black	Black	
152 M	Black	Green	
152 N	Black	Green	Green

## YS Series:

Part Number	DC Spark-Over Voltage Vs(V)	Insulation Resistance IR(OM)/DC	Electrostatic Capacitance 1KHZ-6Vmax C(pf)	Surge Current Capacity 8/20us	Surge Life Test
YS-201 M	200 (160~ 240)	>100M/100V	< 0.8	1000A	8/20usec 100A >300Times
YS-201 N	200 (140~ 260)				
YS-251 M	250 (200~300)				
YS-301 L	300 (255~ 345)				
YS-301 M	300 (240~ 360)				
YS-301 N	300 (210~ 390)				
YS-401 M	400 (320~ 480)				
YS-451 M	450 (360~ 540)	>100M/250V			
YS-501 M	500 (400~ 600)				
YS-551 M	550 (440~ 660)				
YS-601 M	600 (480~ 720)				
YS-701 M	700 (560~ 840)				
YS-102 M	1000 (800~ 1200)				
YS-122 M	1200 (960~ 1440)				
YS-152 M	1500 (1200~1800)				

### Dimension




### Color

Part Number	Color Code 1	Color Code 2
201 M	Red	
201 N	Red	Red
251	Red	Green
301 M,L	Orange	
301 N	Orange	Orange
401	Yellow	
451	Yellow	Green
501	Green	
551	Green	Green
601	Blue	
701	Purple	
102	Black	
122	Black	Red
152	Black	Green

# YA Series:

Part Number	DC Spark-Over Voltage	Insulation Resistance	Electrostatic Capacitance	Surge current capacity	Surge Life
	V <sub>s</sub> (V)		1KHZ-6Vmax		
		IR(OM)/DC	C(pf)	8/20us	Test
YA-141 N	140 (98~182)	>100M/50V	< 0.8	3000A	8/20us 150A >300Times
YA-231 N	230 (161~299)				
YA-251 N	250 (175~325)				
YA-301 L	300 (245~345)	>100M/250V			
YA-351 M	350 (280~420)				
YA-501 M	500 (400~600)				
YA-501 N	500 (350~650)				
YA-701 M	700 (560~840)				
YA-102 M	1000 (800~1200)				
YA-152 M	1500 (1200~1800)				
YA-202 M	2000 (1600~2400)				
YA-242 M	2400 (1920~2800)				
YA-302 M	3000 (2400~3600)				
YA-362 M	3600 (2880~4320)				
YA-402 M	4000 (3200~4800)	>100M/1000V			
YA-452 M	4500 (3600~5400)				
YA-502 M	5000 (4000~6000)				
YA-602 M	6000 (4800~7200)				

## Dimension



## Color


Part Number	Color Code1	Color Code 2	Color Code 3
141	White	Yellow	
231	Red	Orange	
251	Red	Green	
301	Orange		
351	Orange	Green	
501	Green		
701	Purple		
102	Brown	Black	Red
152	Brown	Green	Red
202	Red	Black	Red
242	Red	Yellow	Red
302	Orange	Black	Red
362	Orange	Blue	Red
402	Yellow	Black	Red
452	Yellow	Green	Red
502	Green	Black	Red
602	Blue	Black	Red




## *TEST METHODS and RESULTS*

ITEM	TEST METHOD	STANDARD
STATIC LIFE	10KV WITH 1500pf CONDENSER IS DISCHARGED THROUGH 2KΩ RESISTOR . 200 TIMES AT AN INTERVAL OF 10 SEC.	RATE-OF-CHANGE, WITHIN±30%. INSULATION RESISTANCE & CAPACITANCE, CONFORMED TO RATED SPEC.
COLD RESISTANCE	MEASUREMENT AFTER -40°C/1000 HRS & NORMAL TEMPERATURE/2 HRS.	FEATURES ARE CONFORMED TO RATED SPEC.
HEAT RESISTANCE	MEASUREMENT AFTER 125°C/1000 HRS & NORMAL TEMPERATURE/2 HRS.	
HUMIDITY RESISTANCE	MEASUREMENT AFTER HUMIDITY 90~95%(45 °C)/1000 HRS & NORMAL TEMP/2 HRS.	
TEMPERATURE CYCLE	10 TIMES REPETITION OF CYCLE -40°C/30MIN→ NORMAL , TEMP/2 MIN →125°C/30 MIN , MESUREMENT AFTER NORMAL TEMP/2 HRS.	
SOLDERABILITY	APPLY FLUX AND IMMERSE IN MOLTEM SOLDER 230±5°C FOR 3 SEC UP TO THE POINT OF 1.5MM FROM BODY . CHECK FOR SOLDER ADHESION.	LEAD WIRE IS EVENLY COVERED BY SOLDER.
SOLDER HEAT	MEASUREMENT AFTER LEAD WIRE IS DIPPED UP TO THE POINT OF 1.5MM FROM BODY INTO 260±5°C SOLDER FOR 10 SEC.	CONFORMED TO RATED SPEC.
PULL STRENGTH	APPLY 0.5KG LOAD FOR 10 SEC.	LEAD SHALL NOT PULL OUT OR SNAP.
FLEXURAL STRENGTH	BEND LEAD WIRE AT THE POINT OF 2MM FROM BODY UNDER 0.25 LOAD AND BACK TO ITS ORIGINAL POINT. REPEAT 1 TIME.	

# Dimensions and Packing Form



## Axial Taping



Symbol	Dimensions	
	YP series	YS series
W	52 ± 0.5	
P	5 ± 0.5	
L1-L2	1 max	
T	6 ± 1	
Z	1.2 max	
R	Terminal must not project from the tape.	
t	3.2 min	
S	0.8 max	
D	$\phi 1.8\pm 0.3$	$\phi 2.6\pm 0.3$
D1	$\phi 0.50\pm 0.05$	$\phi 0.70\pm 0.05$
L	3.8±0.5	4.0±0.5

◆各部名稱 PART NUMBER SYSTEM

**B**

<b>B</b>	Bulk
<b>A</b>	Axial
<b>R</b>	Radial

**P**

<b>P</b>	Pouch
<b>F</b>	Flat pack
<b>T</b>	Taping


◆包裝形態 PACKING FORM

型 STYLE	型態 FORM	數量 UNITY QUANTITY
B P	Bulk Packing	500 pcs/pouch
A F	Axial Taping	5000 pcs/box
R T	Radial Taping	2000 pcs/box


◆ MARKING

Color code	
Part Number	
紅 Red	2 0 1
紅+綠 Red+Green	2 5 1
橙 Orange	3 0 1
黃 Yellow	4 0 1

Radial Taping (-RT)



Flat pack



Unit : mm

A	68
B	45 - 125
C	250 - 610

記號 Symbol	寸法 Dimensions(mm)	
	Y P SERIES	Y S SERIES
P	12.7±1.0	
P0	12.7±0.3	
P1	3.85±0.5	
P2	6.35±1.3	
F	5.0±0.5	
W	1.8+1.0-0.5	
W1	9.0±0.5	
H0	1.6±0.5	
H1	32.2 以下(32.25MAX)	
D0	φ4.0±0.2	
D	φ1.8±0.3	φ2.6±0.3
D1	φ0.50±0.05	φ0.70±0.05
L	3.8±0.5	4.0±0.5

File E179423

Vol 1

Issued 01/14/98  
Revised



FOLLOW-UP SERVICE PROCEDURE  
(TYPE R)

COMPONENT - ISOLATED LOOP CIRCUIT PROTECTORS  
(OVGQ2)

Manufacturer: B L KOGYO INC  
(395238-001) 15-2 HARAKI 3-CROME  
ICHIKAWA-SHI  
CHIRA-KEN 272 JAPAN

Applicant: SAME AS MANUFACTURER  
(395238-001) - ooo ♪

Recognized Company: SAME AS MANUFACTURER  
(395238-001)

This Procedure authorizes the above Manufacturer to use the marking specified by Underwriters Laboratories Inc. only on products covered by this Procedure, in accordance with the applicable Follow-Up Service Agreement.

The prescribed Mark or Marking shall be used only at the above manufacturing location on such products which comply with this Procedure and any other applicable requirements.

The Procedure contains information for the use of the above named Manufacturer and representatives of Underwriters Laboratories Inc. and is not to be used for any other purpose. It is lent to the Manufacturer with the understanding that it is not to be copied, either wholly or in part, and that it will be returned to Underwriters Laboratories Inc. upon request.

This PROCEDURE, and any subsequent revisions, is the property of UNDERWRITERS LABORATORIES INC. and is not transferable.

UNDERWRITERS LABORATORIES INC.

Vice President, Follow-Up Services

N

A not-for-profit organization  
dedicated to public safety and  
committed to quality service



1285 Walt Whitman Road  
Melville, New York 11747-308  
(516) 271-6200  
FAX No. (516) 271-8259/8260  
MCI Mail No. 255-3315  
Telex No. 6852015



File E179423  
Project 97ME62776

January 20, 1998

REPORT

on

COMPONENT - ISOLATED LOOP CIRCUIT PROTECTOR

BL Kogyo  
Chiba-Ken, Japan

Copyright © 1997 Underwriters Laboratories Inc.

Underwriters Laboratories Inc. authorizes the above named company to reproduce this Report provided it is reproduced in its entirety.

RLS\_MEL\183241

A not-for-profit organization  
dedicated to public safety and  
committed to quality service

I N D E X

<u>Product</u>	<u>Model Number</u>	<u>Section</u>	<u>Report Date</u>
Isolated Loop Circuit Protector: Gas Tube	Series YS consisting of the following models: YS-201M YS-251M YS-301M YS-401M YS-501M YS-701M	1	1-14-98
Isolated Loop Circuit Protector: Gas Tube	Series YP consisting of the following models: YP-201M YP-241M YP-251M YP-301M YP-401M YP-501M	2	